



EL6LB Installation Instructions

Product Overview:

Add even more light to your bike! The Eagle Lights Elite Series LED Light bar produces a super bright spot light beam pattern to be used in conjunction with the headlight. The mounting bracket is included for securing to the triple tree using the factory headlamp mounting bolt on 06-17 Harley-Davidson Dyna with 49 mm front ends, 00-17 Softail with 41 mm front ends.

Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes.

Required Tools

- Philips-Head Screwdriver

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for a typical installation on most Harley Davidson models. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

**WARNING!**

- To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.
1. Install the light bar onto the fork.
 - a. Using the provided hardware, mount the light between forks on the triple tree.
 2. Route the wiring harness from the light to the battery.
 - a. Ensure that it does not come into contact with any moving parts.
 - b. Place the switch for the light in a convenient place. Many times this will be on the frame rail or on the triple tree itself.
 3. Connect the light to the wiring harness.
 4. Connect the red wire to the battery's positive terminal.
 5. Connect the black wire to the battery's negative terminal.
 6. Reconnect the negative battery terminal.
 7. Test the LED light.