



ELH Horn Instructions.

Product Overview:

Below are steps for a typical installation on most Harley Davidson models. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

| WARNING! | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.• Wear eye protection. | |

- **Step 1:** Remove the seat and disconnect the negative battery cable.
- **Step 2:** Remove the existing horn ,but do **not remove** the mounting stud and **isolator bushing**.
- **Step 3:** Slide the provided heat shrink over both negative and positive wires and connectors . Connect the positive lead from the bike (red on most applications) to the SONICSHIELD positive terminal (left). Connect the negative lead from the bike (black on most applications) to the SONICSHIELD negative terminal (right).
 - Most models include spade connectors that will connect directly to the SONICSHIELD. If your bike does not have them, the leads will need to be spliced to the unit.
- **Step 4:** Mount horn to bike with stock hardware.
- **Step 5:** Reconnect battery negative lead.
- **Step 6:** Test horn