

SPECTRALSHIFT Under Glow Kit Instructions.

Product Overview:

Below are steps for a typical installation on most bikes. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:



WARNING!



- To prevent possible electrical shock, disconnect the negative battery terminal before installing this
 product.
- Wear eye protection.
- 1. Remove saddlebags (if applicable), Remove side covers (if applicable), remove front fender and remove tank. This is to help you route the wires. You may be able to route them without doing this, but removing them may make it easier depending on your motorcycle model.
- 2. Connect the module and test unit.
 - a. From the main module, there will be three wires: red, white, black.
 - i. Black connects to ground battery negative.
 - ii. Red connects to battery positive.
 - iii. White (optional) connects to the brake light positive. This will make all the LEDs light up red when braking for enhanced visibility.
 - b. With the remote in hand, test the light strips before installation.
 - i. The A button will cycle colors.
 - ii. The B button will turn on / off the strobe effect
 - iii. The C button will turn on / off the breathe effect.
 - iv. The D button will turn on / off the unit.
- 3. After verifying, you will need to plan out routing for the wiring. A typical installation will look like this:
 - a. 2 Small Strips on the inner front fender.
 - b. 2 Medium Strips on underside of the gas tank

- c. 2 Long Strips underneath the bike on the lower frame.
- d. 2 Long Strings underneath the saddlebag frame rails.
- 4. When mounting the strips, we HIGHLY recommend cleaning the surface. Remove the film on the back of the light strip and firmly press it onto the surface.
- 5. Ensure all wiring is away from moving parts on the motorcycle after installation.