



FTS-B Installation Instructions

Product Overview:

The Eagle Lights Wrap-Around style turn signals are a great and easy addition to your bike. With an easy attachment method, bright and highly visible turn signal, they will help you be seen on the road.



Tools Required:

- Cleaning Solution

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

Below are steps for a typical installation on most motorcycle models. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

WARNING!	
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.• Wear eye protection.	

1. On the unit there will be two wires. The colors will be black and yellow.
 - a. The black wire will be the ground wire. Connect by soldering or splicing the black wire to the ground for the turn signal on the motorcycle.

2

- b. The yellow wire is for a standard turn signal blink functionality. It will blink on and off at the same rate.
2. Clean the surface where you wish to place the turn signal.
3. Remove the 3M sticker covering and place it on the motorcycle.
4. After positioning the turn signal on the fork, connect the zip tie portion together tightly.
5. Repeat steps for the other side.
6. Test turn signal functionality
7. If you experience a faster than normal turn signal function, you can install a load resistor (PN EL60WR) to slow it down. Sold separately.