



# 9400JLT-S Installation Instructions

## Product Overview:

The Eagle Lights plug and play LED tail lights for JEEP JL models! No additional adapters or wiring needed.

## Typical Installation

Normal installation requires only a few tools, takes less than 45 minutes and requires no wiring on most installations.

## Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at [Support@EagleLights.com](mailto:Support@EagleLights.com).

## Installation:

Below are steps for typical installations on most V-Rod models. Steps may be different depending on the model and year of Jeep JL. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

 <b>WARNING!</b> 
<ul style="list-style-type: none"><li>• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.</li></ul>

- Open the tailgate.
- Remove the panel from the inside of the Jeep. This allows you to access the screw holding on the tail light.
- Once the cap is removed, use a T30 Torx Bit to remove the screw holding the tail light. CAUTION: Stock screw is made from plastic. It is easy to strip. If you do strip it, you can try to use a 10mm to remove the screw.
- Pull the tail light straight out toward you.

## 2

- Disconnect the tail light from the Jeep.
- Get a phillips head screwdriver and remove the bracket from the back of the original light. There will be 3 screws holding it onto the original light.
- If you have the blind spot monitoring system, remove the bracket beneath the main bracke you just took off. It is held on with two screws.
- Install the OEM bracket onto the new light with the stock hardware.
- Bolt load resistor onto L bracket.
- Attach clips to the L bracket.
- Attach the L bracket to the inside of the Jeep. Keep it away from wires as it can become hot.
- Connect LED tail light harness to Jeep wiring harness.
- Repeat for the other tail light.
- Test brake / turn / running and reverse lights.