



Eagle Lights SBL1B-R Instructions

Included Parts:

- SBL2
- Module and Harness

Warning!

For models WITH main fuse:

To prevent accidental vehicle start-up, remove main fuse before proceeding.

For models WITHOUT main fuse:

To prevent accidental vehicle start-up, disconnect negative (-) battery cable before proceeding.

Installation

Read and understand all steps in the instructions before starting the installation.

Step 1:

Remove saddlebag reflectors if they are installed on the bike.

Step 2:

Clean the saddlebag where the unit will be installed. Clear with a 1 to 1 mix of alcohol and water. Allow it to completely dry.

Step 3:

Position the light so the edge is covered by the lid of the saddlebag.

Step 4:

Mark the location with a pencil.

Step 5:

Peel off the tape film from the back and install it in the location marked earlier. Apply firm and even pressure to the light. Do NOT use extreme pressure over the lens.

Step 6

Remove the saddle bag.

Step 7:

Route the wiring along the vehicle side of the saddlebag.

Step 8:

Repeat for other side.

PIN THE HARNESS:

The small white connectors are labeled with numbers.

- Plug green wire into pin one.
- Plug in the black wire into pin two.
- Plug the red wire into pin three.

INSTALL WIRING

Step 1:

Run the wiring through the saddlebag and underneath the seat.

Step 2:

Locate the main lighting wiring harness.

Step 3:

Two harnesses are included in the kit for the different models.

Step 4:

Connect the harness inline with the main lighting harness.

Step 5:

Connect the saddlebag lights to the main harness. Test both the left and right lights.