

## **SBL5B Installation Instructions**

## Product Overview:

Eagle Lights Filler Panel LED Conversion Kit is an LED brake, running, turn signal light system for your 2014 or newer Harley Touring models. They easily bolt into the opening left when the saddlebag / fender filler panel is removed and they will plug directly into the existing harness. Once installed, your Bagger will have two extremely noticeable LED panels that function as full running lights, brake lights, and turn signals.

## Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

## Installation:

Below are steps for a typical installation on most Harley Davidson models. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.



1. Remove the filler panel covers if installed.

2. Remove the saddlebags.



3. Remove the seat





- 3
- 4. Remove the bottom bolts from the filler panel opening.



5. Install the light using the stock hardware by placing it through the back side of the panel opening.





6. Routing the wiring under the seat.



- 7. Connect the wiring harness to the motorcycle rear lighting harness. If the turn signals are reversed when hitting the turn signals, swap the left and right harness on the extension harness.
- 8. Test the lights brake running and turn functions again to ensure the left and right turn signals are on the correct side.
- 9. Go back to the wiring and secure it to the inside of the fender. It has to be secured so that it will not hit the tire.
- 10. Reinstall the saddlebags.

