

## TSM1 Installation Instructions

## Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

## Installation:

Please ensure you have read through the instructions and understand them clearly before attempting the installation.

## WARNING!

 To prevent possible electrical shock, disconnect the negative battery terminal before installing this product. Park the bike on a level surface.

Using an open ended wrench, remove the bolt on the bottom of the mirror.









Remove the stock mirror.

Remove all screws and undo the cover of the turn signal controls.

Remove the top part of the cover and place to the side.


Find the turn signal positive wire. On most models it will either be purple or brown depending. Strip back the wire. We will solder to this wire later.

Get the clutch side mirror. Place one of the washers on the mirror and insert it into the mount for the mirror on the handle bar.

There will be a separate white wire included in the box with an eyelet. This will be connected to the ground. Find the black wire on the bike and connect it to it. Place the eyelet on the stem for the mirror.











Replace the stock turn signal bracket over the mirror stem and then use the provided nut to secure it back on.

Route the wire to the turn signal positive wire that was stripped in the previous step. Cut the wire to length and strip the end of the mirror wire.

Add shrink wrap over the wire end and then solder the wires.

Push the wire back into the cover.

Reinstall the cover. Then repeat the steps for the other side.











