



x

x

5 ¾" Headlight Instructions for Triumph Rocket III

Product Overview:

Below are steps for a typical installation on most motorcycles with 5 ¾" headlights. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

▲	WARNING!	▲
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.• Wear eye protection.		

- **Step 1:** Remove the beauty ring from both headlights. Set hardware aside.
- **Step 2:** Remove the stock headlight reflector and unplug the stock bulb from the motorcycle. Set all hardware aside. (For more detailed instructions, consult the operating manual for the Rocket III.)
- **Step 3:** Plug in LED light to the motorcycle.
- **Step 4:** Reinstall into the bucket with stock hardware.
- **Step 5:** Reinstall beauty ring with stock hardware.
- **Step 6:** Repeat steps 3 - 5 for installing the second light.
- **Step 7:** Test high and low beam functions.