



# VTX Turn Signal Installation Instructions

## Typical Installation

Normal installation requires only a few tools, takes less than 15 minutes.

### Required Tools



- Philips-Head Screwdriver

## Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation. If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at [Support@EagleLights.com](mailto:Support@EagleLights.com).

## Installation:


Below are steps for a typical installation on most VTX models. Steps may be different depending on the model. Please ensure you have read through the instructions and understand them clearly before attempting the installation.

 <b>WARNING!</b> 
<ul style="list-style-type: none"><li>• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.</li></ul>


1. Remove both screws on the turn signal lens.
2. Remove the lens.
3. Remove the stock bulb.
4. Remove the guide plate on the inside of the turn signal. It can be removed by hand or with a set of needle-nose pliers.
5. Insert LED light in socket. Orient the backing plate into the housing.
6. Place the new provided lens onto the housing over the LED. Reattach with stock screws from step one.
7. Repeat steps 1-6 on the other side.

- If the turn signals flash faster than stock, you will need a set of load resistors. The part number needed will be EL60WR. Only one set is needed for the motorcycle.

## HOW TO CONNECT



For 1156, 3156 or 7440



For 1157, 3157 or 7443

