

Eagle Lights Honda Valkyrie Headlight Installation Instructions

Included Parts:

8700 Honda Valkyrie Headlight Honda Valkyrie Bracket

Warning!

For models WITH main fuse:

To prevent accidental vehicle start-up, which could cause death or serious injury, remove main fuse before proceeding.

For models WITHOUT main fuse:

To prevent accidental vehicle start-up, which could cause death or serious injury, disconnect negative (-) battery cable before proceeding.

Common Tools Required

1 - Screwdiver

LED Headlight Installation

Remove the beauty ring on the headlight:

- On the bottom left and bottom right of the stock headlight, remove the two screws with a philips-head screwdriver.
- Holding the headlight from the bottom on the housing, gently pull the headlight from the bottom. The headlight will "pop" out.
- Remove the connection from the back of the housing.

Remove the reflector from stock OEM headlight:

 There are a total of four screws that need to removed from the headlight to remove the reflector.

Bottom Screw:



Top Screw:



IMPORTANT INSTALLATION NOTE

Do not throw away the original screw for the top and bottom of the headlight. They will have a collar on them as well. They will be reused in the installation.

Two Screw On Mount:



Eagle Lights Honda Valkyrie Headlight Installation Instructions



Now the reflector housing can be removed from the mount. It should lift directly off of the reflector.

The ring will come pre-installed on the headlight.

Reinstalling the headlight inside the OEM housing:

 Place the LED headlight with the bracket on the inside of the housing. The top hole on the bracket should match up with the black bracket on the the OEM housing



The top and bottom tabs will mount with the existing OEM bolts. Put the two of the washers provided on each of the bolts

before installing. Screw in the bottom and bottom sections.

Bottom Screw with washers:



Top Screw with washers



The two bolts will now need to be attached to the adjustment tabs. Used the provided hardware.

Two adjustment tab bolts:



Eagle Lights Honda Valkyrie Headlight Installation Instructions



Reinstalling Light into Motorcycle:

- Plug the headlight wiring into the OEM wiring harness.
- Make sure the tabs on the bottom on the light align with the holes.
- Snap the light back into the housingScrew back in the two bolts to secure it to the housing.