



x

x

5 3/4" Headlight Installation Instructions for Yamaha Motorcycles.

Product Overview:



Below are steps for a typical installation on most motorcycles with 5 3/4" headlights. Steps may be different depending on the model and year of your motorcycle. Ensure you have read through the instructions and understand them clearly before attempting the installation.

Installation Warning

If you feel uncomfortable installing this product, we recommend having a professional complete the installation. Eagle Lights LLC is not liable for any damage to the product or vehicle due to an improper installation.

If you have questions about the installation, please feel free to call us at 1-800-921-3162 or email us at Support@EagleLights.com.

Installation:

	WARNING!	
<ul style="list-style-type: none">• To prevent possible electrical shock, disconnect the negative battery terminal before installing this product.• Wear eye protection.		

- Install the triangle bracket on the headlight with the provided hardware.
- Remove the stock headlight from the motorcycle with the two 4mm on the bottom on the trim ring on either side of the headlight bucket.
- Unplug the assembly from the bike.
- Remove the reflector unit from the retaining ring by unscrewing the spring adjustment and the top and bottom bolt.
- Install the headlight into the front trim ring using the stock hardware from used to remove the original headlight assembly.
 - Note the top of the trim ring by the protrusion at the top of the ring.
- Connect the plug from the headlight to the motorcycle.
- Reinstall the headlight with the trim ring to the motorcycle.
- Test low beam and high beam functions.