

COLLECTION:	Wool and PET Felt Wall Flats
USE:	Internal decoration of walls and acoustic control
MATERIAL:	Overlay - 20-40% Wool blend with rayon overlay or PET (polyethylene terephthalate) Felt overlay produced from 100% post-consumer recycled plastic bottles. Base Panel - Bagasse Paper Pulp (natural bleached sugarcane pulp) from 100% pre-consumer waste containing no chemical fillers, no VOC's, and no urea-formaldehyde.
SIZE:	18 x 18 in. (457 x 457 mm) or 19.7 x 19.7 in. (500 x 500 mm) in with +/- 0.5 mm tolerance sideways per 18 in.
WEIGHT:	300 grams (=/+ 275 gr =/- 280 gr)
THICKNESS:	Based on weight of 300 grams - Approx 1.75 - 2 mm (1 model = 1 batch = +/- tolerance of 0.05 mm)
HEIGHT:	Thickness of panel + 15 mm (Total approx 17 mm)
SURFACE:	Smooth without cracks
CUTTING EDGE:	90 degrees with +/- 0.5 mm tolerance sideways per 500 mm and +/- 0.7 mm diagonal
TREATMENT:	Natural water and oil resistance agents added
FIRE RATING:	Commercial Panels With An ASTM E84 Class A Rating are available. Please contact us for pricing, minimum order requirements, and additional information.
EMMISSION:	Base Panel - Formaldehyde <5 mg/kg determined according to the gas analysis method pursuant to DIN EN 12149 Vinyl Chloride <0,1 mg/kg determined according to the gas analysis method pursuant to DIN EN 12149 No Release of Heavy Metals determined according to the gas analysis method pursuant to DIN EN 12149
RETAIL PACK:	18 in Panels = 8 panels covers 18 sq. ft. 19.7 in. Panels = 8 panels covers 21.6 sq. ft.
INSTALL ADHESIVE:	3M Fastbond Contact Adhesive 30NF Neutral (Meets ASTM E84 Class A Requirements) (Greenguard Certified) or DAP Weldwood Low Odor Contact Cement (see installation instructions) or Semi-Permanent Installation with Inhabit Peel + Stick Tape (see installation instructions)