

## **PRODUCT SPECIFICATIONS**

COLLECTION: Planks

USE: Internal decoration of walls

MATERIAL: Solid Vinyl with full coverage 3M acrylic scrim reinforced PSA adhesive

FINISH Polyurethane protective coating

**PLANK SIZE:** 36 x 6 in. or 48 x 6 in.

**WEIGHT:** 2 mm 36 x 6 in. - 1 lb. / 3 mm 36 x 6 in. - 1.8 lb.

**THICKNESS:** 2 mm (0.120 in.), 3 mm (0.20 in.) or 2 + 3 mm Blend

SURFACE: Matte textured

FIRE RATING: 2 mm Only - Class A (ASTM E 84), Flame Spread Index:10, Smoke Developed Index: 450.

EMMISSION: Certified Low Emitting – Material LEED EQc4.3 - Meets Guidelines

Certified Low Emitting – Adhesive LEED EQc4.1 - Meets Guidelines

Indoor Air Quality – Material FloorScore® - Meets Guidelines\*

Indoor Air Quality CHPS 01350 - Meets Guidelines

PERFORMANCE: Chemical Resistance ASTM F 925 No more than slight change in surface dulling, attack or stain

Resistance to Heat ASTM F 1514  $\Delta$ E  $\leq$  8 Pass Resistance to Light ASTM F 1515  $\Delta$ E  $\leq$  8 Pass

Flexibility ASTM F 137 ≤ 1.0 in., no cracks or breaks Pass

Dimensional Stability ASTM F 2199 0.02017 in. max. Exceeds per linear foot

Static Coefficient of Friction/Slip ASTM D 2047 ≥ 0.50 Pass

SHIPPING PACK: 2 mm 36 x 6 in. - Maximum 54 sq. ft. / carton

3 mm 36 x 6 in - Maximum 36 sq. ft. / carton

2+3 mm Blend 36 in x 6 in. - Maximum 42 sq. ft. / carton