

COLLECTION:	Planks
USE:	Internal decoration of walls
MATERIAL:	Solid Vinyl
FINISH:	Polyurethane protective coating
PLANK SIZE:	36 x 6 in. or 48 x 6 in.
WEIGHT:	2 mm 36 x 6 in. - 1 lb. / 3 mm 36 x 6 in. - 1.8 lb.
THICKNESS:	2 mm (0.120 in.) , 3 mm (0.20 in.) or 2 + 3 mm Blend
SURFACE:	Matte textured
FIRE RATING:	2 mm Only - Class A (ASTM E 84), Flame Spread Index:10, Smoke Developed Index: 450.
EMMISSION:	Certified Low Emitting – Material LEED EQc4.3 - Meets Guidelines Certified Low Emitting – Adhesive LEED EQc4.1 - Meets Guidelines Indoor Air Quality – Material FloorScore® - Meets Guidelines* Indoor Air Quality CHPS 01350 - Meets Guidelines
PERFORMANCE:	Chemical Resistance ASTM F 925 No more than slight change in surface dulling, attack or stain Resistance to Heat ASTM F 1514 $\Delta E \leq 8$ Pass Resistance to Light ASTM F 1515 $\Delta E \leq 8$ Pass Flexibility ASTM F 137 ≤ 1.0 in., no cracks or breaks Pass Dimensional Stability ASTM F 2199 0.02017 in. max. Exceeds per linear foot Static Coefficient of Friction/Slip ASTM D 2047 ≥ 0.50 Pass
SHIPPING PACK:	2 mm 36 x 6 in. - Maximum 54 sq. ft. / carton 3 mm 36 x 6 in. - Maximum 36 sq. ft. / carton 2+3 mm Blend 36 in x 6 in. - Maximum 42 sq. ft. / carton

888-830-5072 inhabitliving.com info@inhabitliving.com