

COLLECTION:	Paintable Wall Flats
USE:	Internal decoration of walls
MATERIAL:	White bagasse paper pulp (natural bleached sugarcane pulp)
SIZE:	18 x 18 in. (457 x 457 mm) or 19.7 x 19.7 in. (500 x 500 mm) in with +/- 0.5 mm tolerance sideways per 18 in.
WEIGHT:	275 grams (=+ 275 gr =/- 280 gr)
THICKNESS:	Based on weight of 275 grams - Approx 1.75 mm (1 model = 1 batch = +/- tolerance of 0.05 mm)
HEIGHT:	Thickness of panel + 15 mm (Total approx 16.75mm)
SURFACE:	Smooth without cracks
CUTTING EDGE:	90 degrees with +/- 0.5 mm tolerance sideways per 500 mm and +/- 0.7 mm diagonal
TREATMENT:	Natural water and oil resistance agents added
FIRE RATING:	ASTM E84 - Class B, Flame: 60 / Smoke: 135. If Class A is needed, a treatment option can be applied by Inhabit. Contact us for details/cost. Or Class A can be achieved by adding a Fire Retardant Paint Additive. Recommend Flamecheck M111PA from Flamecheck International.
EMMISSION:	Formaldehyde <5 mg/kg determined according to the gas analysis method pursuant to DIN EN 12149 Vinyl Chloride <0,1 mg/kg determined according to the gas analysis method pursuant to DIN EN 12149 No Release of Heavy Metals determined according to the gas analysis method pursuant to DIN EN 12149
RETAIL PACK:	18 in Panels = 10 panels covers 22.5 sq. ft. 7 lb./pack / Master Pack: 4 Retail Packs 28 lb./carton 19.7 in. Panels = 12 panels covers 32.2 sq. ft. 9 lb./pack/ Master Pack: 3 Retail Packs 28 lb./pack
INSTALL ADHESIVE:	3M Fastbond Contact Adhesive 30NF Neutral (Meets ASTM E84 Class A Requirements) (Greenguard Certified) or DAP Weldwood Low Odor Contact Cement (see installation instructions)
INSTALL FINISHING:	Latex/Water-Based Bonding Primer and Latex Paint