

KBM 50 Q

Metal core drilling unit up to 50 mm

Order number:: 7 270 41 61 24 1



Lightweight and incredibly easy to use, with 2-speed gearbox for efficient drilling in the workshop and on the construction site.

- Compact with high functionality for universal use on construction site and in the workshop.
- Simple operating concept avoids mix-ups and can be clearly seen by the user.
- Double drill motor guide for use with very large drilling tools.
- Reversible rotation.
- Electronic speed setting.
- FEIN high-power motor with stable speed.
- High magnetic holding force.
- Convenient magnetic holding force display.
- Integrated coolant tank.
- Feed handwheel can be moved from one side to the other.



KBM 50 Q

Metal core drilling unit up to 50 mm

Order number:: 7 270 41 61 24 1

Technical data

Carbide core drill bit max. diameter	50 mm
HSS core drill max. Ø	40 mm
Core drill, drilling depth max.	50 mm
Twist drill max. Ø	16 mm
Tapping	M 16
Countersinking max. Ø	31 mm
Reaming max. Ø	16 mm
Input	1 200 W
Output	640 W
1st gear	130-260 rpm
2nd gear	260-520 rpm
Core drill holder	QuickIN (3/4 in Weldon: AU,CA,US,UK)
Stroke	145 mm
Total stroke range	315 mm
Magnetic holding power	12 500 N
Magnetic foot dimensions	195 x 90 mm
Cable with plug	4 m
Weight according to EPTA	13,2 kg
Corded	X

Included in price::

1 case
1 coolant tank
1 lashing strap
1 swarf hook
1 centering pin
1 contact guard