

Product information

18V Impact Wrench LXT



DTW281RMJ

Battery Type	Lithium-ion
Voltage	18 v
Battery quantity (4.0Ah)	2
Driving Shank	1/2" Square
Blows per Minute (Hi) - ipm	0 - 3500 ipm
Blows per Minute (Med) - ipm	0 - 2600 ipm
Blows per Minute (Lo) - ipm	0 - 1800 ipm
Standard Bolt	M10-M20
High Tensile Bolt	M10-M16
Maximum Output	280 w
No Load Speed (hard/med/soft)	0-2800 / 2100 / 1600 rpm
Max Fastening Torque	280 Nm
Vibration: Fastening Bolt	11.5 m/sec ²
Vibration K factor	1.5 m/sec ²
Net weight	1.7 kg



STANDARD EQUIPMENT: 196399-0 BATTERY BL1840 18V Li-ion, 821550-0 MAKPAC CONNECTOR CASE (TYPE 2), 837670-0 INNER TRAY, DC18RC DC18RC COMPACT CHARGER

- Electronic 3-stage impact power selection to reduce fault tightening.
- Battery fuel gauge
- Variable speed control by trigger
- LED Job light with pre-glow and afterglow functions
- Forward/reverse rotation
- Electric brake
- Ergonomic soft grip.
- Compact overall length.

Details correct as of: 16-5-2016

Makita reserve the right to change specifications at any time owing to their policy of constant improvement.

Accessories shown are not necessarily supplied.

www.makita.com