

JUJU PAPERS

JUJU PAPERS TYPE II MYLAR SPECIFICATIONS

PRODUCT DIMENSIONS

54" WIDE PRODUCT

52" WIDE PRINTED AREA

50" PATTERN WIDTH (ONE INCH OF BLEED ON EACH SIDE, and ONE INCH OF SELVAGE BEYOND THAT)

PHYSICAL PROPERTIES

Product Weight: 21 oz. per lineal yd., (13oz. per sq. yd.)

Vinyl Weight: 16.5 oz. per lineal yd.

Polyester Weight: 1.5 oz. per lineal yd.

Fabric Weight: 3 oz. per lineal yd.

Thickness: 0.017 in.

Fabric: Nonwoven

BREAKING STRENGTHS, LBS. FORCE

Machine Direction-warp: Exceeds Type II minimum of 50 lbs.

Cross Machine Direction-fill: Exceeds Type II minimum of 55 lbs.

TEARING STRENGTH, SCALE

Machine Direction-warp: Exceeds Type II minimum of 25 lbs.

Cross Machine Direction-fill: Exceeds Type II minimum of 25 lbs.

Cold Crack Resistance: At 20°F - No changeHeat Aging

7 Days at 158°F: No change

FIRE TESTING

ASTM-E84 Tunnel Test Class A

NFPA Life Safety Code 101 Class A

*Meets or exceeds requirements for flame spread,smoke developments and flashover.

*Cadmium and Lead Free Formulation

SPECIFICATIONS

FEDERAL SPECIFICATION: CCC-408-D Type II

WA SPECIFICATION: W-101 Type II

ASTM-G21 SPECIFICATIONS Passed all requirements

ENVIRONMENTAL

Meets or exceeds EN12149 A,B,C - the EU Toxicity requirement for heavy metals(including Cadmium, Mercury, Lead and Antimony), and formaldehyde under EN15102

Manufactured without the use of Brominated Flame retardants

Indoor Air Quality

- Manufactured with Low VOC Vinyl- Meets California CDPH Standard for Schools and Offices
- Tested per CA 01350LEED
- Can contribute to Paragraphs EQ 4.1 for low emitting materials and MR 5.1 for regional materials