

JUJU PAPERS

JUJU PAPERS TYPE II VINYL WALLCOVERINGS SPECIFICATIONS

PRODUCT DIMENSIONS

54" wide product

52" wide printed area

50" pattern width (one inch of bleed on each side, and one inch of selvage beyond that)

PHYSICAL PROPERTIES

Product Weight: 20 oz. per lineal yd., (13oz. per sq. yd.)

Vinyl Weight: 17 oz. per lineal yd.

Fabric Weight: 3 oz. per lineal yd.

Thickness: 0.015 to 0.030 in. *depending on texture

Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven *depending on texture

BREAKING STRENGTHS, LBS. FORCE

Machine Direction-warp:

*Exceeds Type II minimum of 50 lbs.

Cross Machine Direction-fill:

*Exceeds Type II minimum of 55 lbs.

TEARING STRENGTH, SCALE

Machine Direction-warp:

*Exceeds Type II minimum of 25lbs.

Cross Machine Direction-fill:

*Exceeds Type II minimum of 25 lbs.

COLD CRACK RESISTANCE @ 20°F

No change

HEAT AGING (7 DAYS @ 158°F)

*Does not become stiff, brittle, discolored, or show loss of grain

SPECIFICATIONS / TESTING / CERTIFICATION

Federal Specification:

*CCC-408-D,C,B,A *Type II *Class A

Wa Specification:

W-101 Type II

FIRE TESTING

ASTM-E84 Tunnel Test Class A

NFPA286 Corner Burn Test Class A

NFPA265 Corner Burn Test Class A

EN15102 Class B

*Meets or exceeds requirements for flame spread, smoke developments and flashover.

MOLD/MILDEW/BACTERIAL RESISTANCE

ASTM-G21 Specifications:

Passed all requirements of CCCW-408-D

ENVIRONMENT

Meets or exceeds EN12149 A,B,C - the EU Toxicity requirement for heavy metals (including Cadmium, Mercury, Lead and Antimony), and formaldehyde under EN15102