

# SCULPTURAL PILLOW SPECIFICATIONS

PRODUCT NAME: FORM PILLOW / INDOOR PILLOW

COVER MATERIAL: 100% New Zealand lambswool

WEIGHT: 131/2 oz/sq yd ±5%  
(201/4 oz/running. yd ±5%)

ABRASION RESISTANCE: ASTM D4157 Wyzenbeek method,  
Heavy Duty Upholstery  
Independently certified to ≥75,000  
double rubs.

FLAMMABILITY: California Technical Bulletin 117 - 2013  
NFPA 260 + UFAC Class 1  
BS 7176 Low Hazard  
ASTM E84 Class 1 or A (Adhered)  
ASTM E84 Class 1 or A (Un-adhered)  
IMO FTP Code (Part 8)  
NFPA 701 when FR treated

COLOR FASTNESS  
TO LIGHT: AATCC-16 (40 hours) Class 4

COLOR FASTNESS  
TO CROCKING: AATCC-8 (Dry: 4, Wet: 3)

Qualifies for LEED v4, BREEAM, WELL Building, and Living Building  
Challenge. LEED Credit Contributor LEED v3 • v4.

Wool facility systems are 0% Waste to landfill. – ISO 14001, ISO 9001,  
OHSAS 18001.

PILLOW FOAM: Low VOC Polyurethane  
HR Foam

Made without ozone depleters.

Made without PBDEs, TDCPP or TCEP (“Tris”)  
flame retardants.

Made without mercury, lead and heavy  
metals.

Made without formaldehyde.

Made without phthalates regulated by the  
Consumer Product Safety Commission.

Low VOC (Volatile Organic Compound)  
emissions for indoor air quality (less than 0.5  
parts per million).

Waste foam created by cutting out the pillow  
shapes is shredded and recycled for use in  
carpet padding.

CERTIFIED BY CERTIPUR-US®

CLIMATE NEUTRAL CERTIFIED PRODUCT

# THATCHER

503.875.0428

SALES@THATCHERSTUDIO.COM