

IRIDESCENT MYLAR WALLCOVERING CARE AND CLEANING

GENERAL CONDITIONS, REMOVING DAY-TO-DAY SOIL

PATINA

Due to the reflective and refractive nature of the product, extra care must be taken to use gentle, even, circular strokes on the entire surface of the material while installing, wiping, smoothing, and finishing this highly reflective material. Installation of the materials in general will cause subtle directional marks as the surface is hung, wiped, and smoothed, and should contribute to an overall, consistent patina. A consistent patina contributes to the added beauty of the material. The patina from touch, use, and installation of this material is not a flaw and is an added feature of the reflective beauty of the material.

Those looking for a perfect, mirror-like, flawless surface should consider using a different product. This material will show subtle directional surface marks which add slight directional light patterns depending on the direction of light upon the product.

Every drop of this material is unique, and will reveal itself to be its own pearl. The dominant colors in the material will vary across the panels and will change over the course of the day, depending on the light.

The material might be affected by mood, and it might reveal one's enemies.

Aggressive scratches, sanding, rough use, abuse, or use of chemicals beyond those fit for normal installation is not considered normal use or installation. Take care to handle materials with consistent circular strokes, in order to create an even and consistent patina finish.

Wipe with a moist cloth or sponge. Do not oversoak the wallcovering surface.

Ordinary dirt and smudges can be removed with a mild soap and warm water. Clean from bottom of wall upward. Rinse thoroughly with clean water from the top down using a sponge. Deeply embossed wallcoverings need extra attention to remove suds or loosened dirt that may lodge in the embossing. Dry wallcovering with a soft lint free cloth or towel.

For more difficult stains that are only surface deep, the use of a stronger detergent is recommended. Always test an inconspicuous area with the stronger detergent to be sure that the surface and ink are not damaged.

DO NOT USE steel wool or powdered abrasives because they can damage the image and textured surface.

DO NOT USE solvents, alcohol, pine oil, or cleaners that contain these products as they can remove the image and damage the textured surface.

When cleaning, always take measures to prevent water from dripping behind molding.

NEVER MIX CLEANING AGENTS TOGETHER, VIOLENT REACTIONS MAY OCCUR.