TYPE II MYLAR WALLCOVERING SPECIFICATIONS

PRODUCT NAME: TYPE II MYLAR WALLCOVERING

PRODUCT DIMENSIONS: 54" wide product

52" wide printed area

50" pattern width (one inch of bleed on each side, and one inch

of selvage beyond that)

PHYSICAL PROPERTIES

Product Weight: 21 oz. per lineal yd., (13oz. per sq. yd.)

Vinyl Weight: 16.5 oz. per lineal yd. Polyester Weight: 1.5 oz. per lineal yd. Fabric Weight: 3 oz. per lineal yd.

Thickness: 0.017 in. Fabric: Non-woven

BREAKING STRENGTH, LBS FORCE

Machine direction-warp: Exceeds Type II minimum of 50 lbs. Cross Machine Direction-Fill: Exceeds Type II minimum of 55 lbs.

TEARING STRENGTH, SCALE

Machine Direction-warp: Exceeds Type II minimum of 25 lbs. Cross Machine Direction-fill: Exceeds Type II minimum of 25 lbs.

Cold Crack Resistance: At 20°F - No change

Heat Aging 7 Days at 158°F: No change

FIRE RATING

ASTM-E84 Tunnel Test: Class A NFPA Life Safety Code 101: Class A

*Meets or exceeds requirements for flame spread, smoke developments and flashover *Cadmium and Lead Free Formulation

SPECIFICATIONS

Federal Specification: CCC-408- D Type II

WA Specification: W-101 Type II ASTM-G21 Specifications: Passed all

requirements

MILDEW / MOLD

ASTM G21 Specifications pass all requirements

ENVIRONMENTAL

CLIMATE NEUTRAL CERTIFIED PRODUCT

Meets or exceeds EN12149 A,B,C - the EU Toxicity requirement for heavy metals (including Cadmium, Mercury, Lead and Antimony), and formaldehyde under EN15102

Manufactured without the use of Brominated Flame retardants

Indoor Air Quality

- Manufactured with Low VOC Vinyl- Meets California CDPH Standard for Schools and Offices
- Tested per CA01350 LEED (CDPH Standard Method v1.2-2017) *Third Party certified by Berkeley Analytical Associates
- Can contribute to Paragraphs EQ 4.1 for low emitting materials and MR 5.1 for regional materials



ENVIRONMENTAL CONTINUED

NSF-342 - Certified for compliance for 20 oz wallcovering constructions

Contributes to LEED v4

Phthalate free formulation

Prop 65 compliant

For non-woven backed constructions:

- 6% post-consumer content in total product using recycled polyester, cellulose
- 50% of backing fiber content is post-consumer fiber

