

TOP-MOUNTED REACH-IN REFRIGERATOR

Los Angeles Office 2460 Peck Road, City of Industry, CA 90601

New Jersey Office 4475 S Clinton Ave South Plainfield, NJ 07080

(562) 568-4060 (215) 808-8239 www.dukersusa.com Info@dukerusa.com

MODEL: D55AR-GS2

Features and Benefits

- * Higher Resistance to Dust , high quality condenser
- * R290 Natrual Refrigerant, promotes faster cool down and efficient energy consumption
- * 3-year parts and labor, 5-year compressor warranty
- * Stainless steel inside and outside, sealed interior floors and rounder cabinet corners for easy cleaning
- * Self-closing doors with stay open feature.
- * Adjustable, heavy duty shelves

Technical Specifications

Voltage/Frequency	115V/60Hz
Refrigerant	R290
Type of Defrost	Automatic
Exterior Finish	Stainless steel
Interior Finish	Stainless steel
Net Weight	463 lbs
Total Capacity	40.74 cu ft
Total Current	8.6A
Climatic Category	4/5
Nema Config.	5-20P









MODEL NO	TEMPERATURE RANGE (°F)	EXTERNAL DIMENSION WXDXH(INCHES)	PACKING, CARTON WXDXH (INCHES)	DOOR	40GP CONTAINER CERTIFICATION
D55AR-GS2	33°F ~ 41°F	551/8" X 325/8" X 803/8"	56¾" X 34¼" X 84¾"	2	21

TOP-MOUNTED REACH-IN REFRIGERATOR

MODEL: D55AR-GS2

Model: D55AR-GS2

115V AC Rated Voltage:

60Hz Rated Frequency:

Total Input Power: 730W

Total Current: 8.6A

40.74 cu ft Total Capacity:

Refrigerant: R290/5.11oz

Climatic Category: 4/5

Protection Type

Design pressure High Side: 300PSIG

Low Side: 150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 463 lbs

NEMA Config 5-20P

STANDARD FEATURES

TOP MOUNT COMPRESSOR

The top mount compressor structure is placed in the coolest possible area, provides quick and easy service R-Series

HIGH QUALITY STEEL

Interior and exterior high quality steel minimizes dents, scratches and rust

HIGH DENSITY POLYURETHANE **INSULATION CFC**

free and high density cell foam is Eco-friendly and more energy efficient

STURDY, CLEAN STAINLESS SHELVING

High quality coated stainless shelves may prevent peel and rust.


SELF-CLOSING DOOR SYSTEM Door Automatically close at 60°


FREEZERS HOLDS 33°F ~ 41°F FOR BEST IN REFRIGERATORS



115/60/1

PLAN VIEW





SIDE VIEW

