

Enhanced Cleanability and Sanitation Features Certified by NSF International - NSF/ANSI 8 - 2010 Standard

Quality Construction

- Hard chromed, special alloy hollow ground knife
- Anodized aluminum construction with seamless edges and radius corners
- Large food carriage and product receiving area
- Top mounted all metal knife sharpener
- Removable, easy-to-clean chute, slice deflector, knife cover & sharpener
- Metal bottom enclosure
- Permanently attached knife ring guard
- Moisture proof, easy-to-clean On/Off switch
- Sealed splash zones for added sanitation and protection of electronics

Warranty

One-year parts and labor

Optional Warranty Extension

Additional one-year warranty on parts and labor inside the continental U.S.

Approved by:

Standard Features

- 0 to 9/16" slice thickness
- Powerful 1/2 HP knife motor
- Motor overload protection with manual reset
- Oversized positive traction grooved belt drive
- Knife cover interlock
- Ergonomically designed, dual purpose handle
- · Smooth stainless steel ball bearing chute slide
- 35° angled food chute
- No voltage release relay system
- Power indicator light


Optional Accessories

- **M**500A Food Fence (11"L x 1 ¹/₈"H)
- SC-LARGE Slicer Cover
- **300014** Vegetable Hopper
- CB Cleaning Brush

Date:

Medium Duty Manual Slicer

G14



SPECIFICATIONS													
Model	Motor	Volts	Amps	Drive Type	Slicing Volume per Day	Cheese Slicing	Blade Diameter	Max Slice	Cu D (Diameter)	Itting Capac W (Width)	ity H (Height)		
G14	1/2 HP	115-60-1	4	Belt	3 Hours	0100% Time	14" (35.56 cm)	9/16" (1.43 cm)	9.75" (24.8 cm)	11.5" (29.2 cm)	10.125" (25.7 cm)		

Cord & Plug: Attached 6 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15 $\begin{pmatrix} I \\ a \end{pmatrix}$

STANDARD FEATURES:

Finish: Stain resistant, heavygauge, anodized aluminum finish is easy to clean.

Motor: 1/2 HP, Powerful fan cooled motor and permanently lubricated ball bearings ensure quiet operation. Thermal overload protection included.

Knife: 14" Hard chromed, special alloy hollow ground knife lasts longer and sharpens easily.

Manual Reset Button: Motor overload protection allows the operator to reset the slicer manually. Top Mounted Sharpener:

All metal construction and top mounted for easy access. Two stone, dual action design allows quick return to a razor sharp edge. Removable for cleaning.

On/Off Controls: Separate On/ Off push buttons are moisture protected and sanitation sealed.

Ball Bearing Chute Slide System: Ball bearing system ensures smooth and easy movement of the food chute assembly. Knife Hub: Knife hub bearings, belt and motor are fully enclosed, protecting them from moisture.

Knife Cover Interlock: Slicer will not operate with the knife cover removed.

Knife Ring Guard: Permanently mounted knife ring guard protects the non-slicing portion of the knife. Slicer table protects leading edge of the knife when completely closed.

Table Rod: Separate tablesupport rod is protected by thetable casting and cover.

Bottom Enclosure: Components are safeguarded by a cover, protecting them from food and other debris.

No Volt Release Relay: Prevents inadvertent activation of the slicer in the event of power interruption.

Slice Deflector: Deflector is securely fastened to the slicer; simple to remove without tools and easy to clean.

Freight Class 85

Rubber Feet: Supplied with nonslip rubber feet.

DIMENSIONS & SHIPPING INFORMATION

Carton reinforced for shipping. The weight and dimensions of reinforced carton are included below and may vary from shipment to shipment.										
Model	Foot Print	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight					
G14	19.5" D x 15.25" W (49.53 cm x 38.7 cm)	28" L x 23" W x 18" H (71 cm x 58 cm x 45.7 cm)	64 lbs. (29 kg)	25" L x 28" W x 38" H (64 cm x 71 cm x 130 cm)	95 lbs. (43 kg)					

Specifications are subject to change without notice.