

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Projec	t :

Model # : Item # :

Qty :

Available W/H :

Approval :

Worktop Refrigerator - Drawers

Worktops Super Deluxe Series

Model : TWR-60SD-D4





____ FEATURES & BENEFITS =___

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Durable stainless steel drawers

Drawers are easy to clean and assemble.

Efficient refrigeration system

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Refrigerator holds 33°F ~ 38°F for the best in food preservation

ATA

								ISO9001:2008
Model	Swing Door	Drawers	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^{\dagger}$ (inches)
TWR-60SD-D4	-	4	16	-	1/3	9.9	312	601/4 x 30 x 331/2

* Depth does not include 1" for rear spacers. † Height does not include 5-7/8" for caster height.

Worktop Refrigerator - Drawers

(unit : inch)

Model : TWR-60SD-D4

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	9.9				
Compressor HP	1/3				
Cord Length ft.	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Net Capacity cu. ft.	16				
Ext. Length Overall in.	601/4 (1530mm)				
Ext. Depth Overall in.*	30 (762mm)				
Ext. Height Overall in. ⁺	331/2 (851mm)				
# of Doors	-				
# of Shelves	-				
Net Weight Ibs.	272				
Gross Weight Ibs.	312				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


* Depth does not include 1" for rear spacers. † Height does not include 5-7/8" for caster height.

• WARRANTY : ³ Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" swivel casters with locks on the front set
- 2.5" dia. casters available ½" diameter & 13 TPI (optional)
- Legs available for all models (optional)
- Door locks available (optional)
- External digital thermometer available (optional)


OPTIONAL ACCESSORIES :

- 2.5" Diameter casters
- 5" Diameter casters
- 6" ABS plastic legs



PLAN VIEW

PLAN VIEW



SIDE VIEW

Ver.201506



- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002





(GERMAN

