

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item#:	Qty:
Available W/H :	
Approval:	

Horizontal Open Display Cases

Low Profile Glass Side Panel

NO PLUMBING REQUIRED

Model: TOM-50L(B) / TOM-50L-SP(-A)





Top display dry case available (optional)





TOM-L-SP-ASolid side panel available

TOM-LB-SF *
Stainless steel front panel available (optional)

___ FEATURES & BENEFITS =__

TOM-50LB

■ Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Glass front shield and side walls optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application.

- LED lighting interior display system
- Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing less heat, while maximizing the visibility in the display area.
- Solid side panels used to ensure durability (TOM-L-SP(-A) models)
- Interior materials available in two standards (TOM-L-SP(-A) models)

Stainless steel interior for sanitary purposes or black coated interior with mirrored sides for maximized display effects.

- Designed to enhance impulsive sales Ideal for eye-catching displays and convenient access with fast service in high traffic area.
- Environmentally friendly, efficient refrigeration system

Turbo Air's refrigerators are designed with oversized and balanced environmentally friendly R-134A (CFC Free) refrigeration. These include large evaporators and condensers for faster cooling and balanced temperature throughout the cabinet.

- Non-peel, durable anti-rust coating on the exterior reduces fingerprints
- Standard back-guard improves airflow
- 300 series stainless steel interior standard including back wall, shelves and deck pans
- Perforated interior back wall and top for improved air flow
- Front air intake and rear air discharge
- Foamed with polyurethane, high-density cell insulation (CFC free)
- Stainless steel front panel available for all model (optional)
- Recommended operating conditions

TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.









Model	CU./FT.	# of Bottom Shelves	НР	AMPS	Crated Weight (lbs.)	L x D x H (inches)
TOM-50L(B) TOM-50L-SP(-A)	11.7	1	1/2	11	505	503/4 x 345/8 x 453/4

Horizontal Open Display Cases

Model: TOM-50L(B) / TOM-50L-SP(-A)

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type				
Full Load Amperes	11			
Compressor HP	1/2			
Refrigerant	R-134A			
DIMENSIONAL DATA				
Net Capacity cu. ft.	11.7			
Ext. Length Overall in.	50 _{3/4} (1289mm)			
Ext. Depth Overall in.	345/8 (880mm)			
Ext. Height Overall in.	45 _{3/4} (1162mm)			
Int. Length Overall in.	483/8 (1229mm)			
Int. Depth Overall in.	24 (610mm)			
Int. Height Overall in.	17 _{1/2} (445mm)			
Net Weight lbs.	376			
Gross Weight lbs.	505			
# of Shelves	1			
Self Size	481/4 x 103/4			


Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 2 Year Parts and Labor Warranty
Additional 3 Year Warranty on Compressor

- Simple plug-in installation
- Patented self-contained system, no plumbing required

■ TOMD-50-L: 50" Non-Refrigerated top display case for Low Profile				
503/4 x 121/4 x 131/4				
483/8 x 91/8 x 113/8				
2.9				
65				




FRONT VIEW


503/4 (1289mm)

PLAN VIEW


(unit: inch)



TOP VIEW



SIDE VIEW



SIDE VIEW (W/ TOMD)

Ver.201501

















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002