

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

# Back Bar

Underbar Equipment Super Deluxe Series

**Model: TBB-1SB-N6** 



# \_\_\_ FEATURES & BENEFITS =\_\_

#### ■ Hydrocarbon Refrigerants (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### ■ Forced air cooling system

Fast cooling and balanced temperature throughout the cabinet.

# Stainless steel countertop and interior

The exterior of cabinet is constructed with heavy gauge reinforced stainless steel countertop and wear-resistant black vinyl coated galvanized steel. Interior is painted galvanized steel with reinforced stainless steel floor. Turbo Air Back Bar model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.

# ■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

#### ■ LED lighting interior

Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing less heat.

#### ■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in beverage preservation













							130 9001.2008 IIILEI LEF	littertek
Model	Swing Door	CU./FT.	1/2 Barrels	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBB-1SB-N6	1	7.5	1	2	1/8	1.3	235	235/8 x 321/8 x 341/2

(unit: inch)

# **Model: TBB-1SB-N6**

ELECTRICAL DATA						
Voltage		115/60/1				
Plug Type		① NEMA 5-15P				
Full Load	Amperes	1.3				
Compress	or HP	1/8				
Refrigerar	nt	R-600a				
Cord Leng	th (ft.)	9				
Lamp (W)		13				
DIMENSIONAL DATA						
Capacity	1/2 Barrels	1				
Сараспу	Cubic Feet	7.5				
Ext. Lengt	h Overall (in.)	23 <sub>5/8</sub> (599mm)				
Ext. Depth	Overall (in.)*	321/8 (816mm)				
Ext. Heigh	t Overall (in.)†	341/2 (875mm)				
Net Weigh	nt (lbs.)	190				
Gross We	ight (lbs.)	235				
# of Swing	Door	1				
# of Shelv	es	2				
Shelf size	(L x D) (in.)	181/2 x 191/2				
# of Caste	rs	4EA				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty
Additional 2 Year Warranty on Compressor

- Self-contained system
- 4" dia. swivel casters standard
- Door locks standard


## ■ OPTIONAL ACCESSORIES:

☐ Additional PE coated wire shelf: P017800100


# **PLAN VIEW**



**PLAN VIEW** 



**FRONT VIEW** 



Ver.20170810











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup> Depth does not include 2" for rear spacers. † Height does not include 5" for caster height.