

Multi-Function Video Test Monitor



Video Test Monitor

4KTESTMON1

- > Designed for installation and maintenance of IP and Analog cameras
- > Composite video (CVBS, TVI, CVI, AHD) and IP video input support with ONVIF Profile S Compliance
- > 7" Touch-Screen, 1920 x 1200 resolution
- > H.265/H.264, 8K video display via mainstream
- > RJ45 Ethernet cable, video level meter and cable trace test support
- > PoE power voltage, PING and IP address searching support
- > 4K, 30fps HDMI input and 4K, 60fps, HDMI output
- > Support VGA input and Wi-Fi connectivity
- > Rechargeable lithium battery and external 12VDC power supply
- > Includes Digital Multimeter

www.univiewtechnology.com

Specifications

Video Test Monitor	
Monitor	7" touch screen
IP Video	1 x RJ-45, 10M/100M auto adjust
Analog Video	1 x BNC input: CVBS, TVI, CVI, AHD 1 x BNC output
Serial Interface	1 x RS-485
HDMI	1 x input and 1 x output
VGA	1 x input
PoE	1 x RJ45, 48V output, maximum 30W
Camera Power	12VDC, 3A output power to camera
Audio	1 x RCA input and 1 x RCA output
Micro SD Slot	8GB card included
Power Supply	12VDC, 2A
Battery	7.6V Lithium polymer battery ,7800mAh
Digital Multimeter	DC and AC voltage measurement, Resistance measurement, Continuity test, Diode measurements, Capacitance measurement, support record data and create report
Operating Temperature	-10°C ~ + 50°C (4°F ~ 122°F)
Operating Humidity	30% ~ 90% RH
Dimensions	255 x 160 x 46mm (10 × 6.3 × 1.8")
Weight	.95kg (2.1lb)

Top View



Bottom View

