20 mm (5035) Impact Sprinkler Technical Specifications

TWSS 20 mm (¾") Male 5035 Plastic Full Circle Impact Sprinkler is constructed from high quality plastics. The Water Sprinkler Shop impact sprinklers offer high distribution uniformity with colour coded bayonet nozzles. Can be a replacement for Naan and other brands.

- Full Range of Nozzles Available
- 20 mm (¾") BSP Male Connection
- Colour-Coded "Click" Bayonet Nozzles.
- Spacing up to 22 Meters
- UV Resistant
- High-Resistance Rotating Joints
- Reach of 13 18 M
- Flow of 1020 3830 L/H
- Working Pressure of 3 5 BAR
- Application Area of a Full circle
- Nozzle / Trajectory Angles of 25º And 20º
- Maximum Stream Height of 2.4 M
- Body Specially Designed For Bayonet Nozzles
- Rotation Will be Constant And Continuous
- Medium Flow Agricultural Impact Sprinkler
- Made of High Quality Plastic And Stainless Steel
- Two Nozzles That Can Consist of One Main Nozzle And a Secondary Nozzle or Plug
- Rotation Time Will Depend on The Pressure And The Nozzles



Drippers
 Sprinklers
 Fertilizer Injectors
 Fittings



ORDERS OVER \$150 FREE SHIPPING WITHIN NEW ZEALAND

Nozzle Diameter Nozzle Colour	Working Pressure BAR	Single Nozzle (Front) Flow Rate M3/H	Double Nozzle (Front/Back) Flow Rate M3/H	Spray Radius M
4.0 + 3.0 Black + Grey	3 4 5	1.02 1.19 1.34	1.45 1.68 1.88	13.0 13.5 14.0
4.5 + 3.0 Brown + Grey	3 4 5	1.29 1.50 1.69	1.66 1.94 2.18	14.0 14.5 15.0
5.0 + 3.0 Purple + Grey	3 4 5	1.58 1.84 2.07	1.95 2.28 2.56	14.5 15.0 16.0
5.5 + 3.0 Orange + Grey	3 4 5	1.91 2.23 2.51	2.29 2.65 3.00	15.0 16.0 16.5
6.0 + 3.0 Red + Grey	3 4 5	2.21 2.57 2.90	2.57 3.00 3.38	15.0 16.5 17.0
6.5 + 3.0 Grey + Grey	3 4 5	2.55 2.97 3.35	2.92 3.40 3.83	16.0 17.0 17.5

- K-Line System & Parts
 Filters
 Valves
 Controllers
- Drippers Sprinklers Fertilizer Injectors Fittings