

SAFETY DATA SHEET

1. Identification

Product identifier	SDA 40-B, 200 Proof
Other means of identification	None.
Recommended use	General purpose solvent.
Recommended restrictions	Refer to the alcohol control authority in which the product is to be used - Canada Revenue Agency (Excise) in Canada, US Tax and Trade Bureau in the US, etc.
Manufacturer/Importer/Supplier/	Distributor information

Company name	YellowBee Packaging and Supplies Inc.
Address	#106, 2880 107 Ave SE
	Calgary, AB T2Z3R7
	Canada
Telephone	(587) 578-3929
Website	yellowbee.ca
Emergency phone number	CANUTEC: (613) 996-6666

2. Hazard identification

Physical hazards	Flammable liquids	Category 2	
Health hazards	Serious eye damage/eye irritation	Category 2	
Label elements			
	\wedge		
.			
Signal word	Danger		
Hazard statement	Highly flammable liquid and vapour. Causes serious eye irritation.		
Precautionary statement			
Prevention	Keep container tightly closed. Ground and bon	uipment. Use non-sparking tools. Take action to	
Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use water fog, alcohol-resistant foam, dry chemical powder, carbon dioxide to extinguish.		
Storage	Store in a well-ventilated place. Keep cool.		
Disposal	Dispose of contents/container in accordance w	vith local/regional/national/international regulations.	
Supplemental information	None.		
Other hazards	None known.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	99.87
Other components below reportable levels			0.13

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapour.

6. Accidental release measures

Specific methods General fire hazards

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (Oo Components	ccupational Health & Safety Code, Sche Type	edule 1, Table 2) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Canada. British Columbia Safety Regulation 296/97,		for Chemical Substances, Occupational Health and
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety A	nd Health Act)
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Ontario OELs. (C	ontrol of Exposure to Biological or Che	emical Agents)
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Canada. Quebec OELs. (N Components	linistry of Labor - Regulation respectin Type	g occupational health and safety) Value
Ethanol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Canada. Saskatchewan O Components	ELs (Occupational Health and Safety R Type	egulations, 1996, Table 21) Value
Ethanol (CAS 64-17-5)	15 minute	1250 ppm
	8 hour	1000 ppm
	No biological exposure limits noted fo	r the ingredient(s).
ological limit values	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.	
ological limit values propriate engineering ntrols	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer exposure limits. If exposure limits hav	naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommende re not been established, maintain airborne levels to an
propriate engineering ntrols	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipment	naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommende re not been established, maintain airborne levels to an ation and safety shower. ent
propriate engineering ntrols	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipment	naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommende re not been established, maintain airborne levels to an ation and safety shower.
propriate engineering ntrols lividual protection measure	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineer exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipment	naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommende re not been established, maintain airborne levels to an ation and safety shower. ent
propriate engineering ntrols lividual protection measure Eye/face protection	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipme Wear safety glasses with side shields Butyl rubber or Viton® gloves are reco	naust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommende re not been established, maintain airborne levels to an ation and safety shower. ent
propriate engineering ntrols lividual protection measure Eye/face protection Skin protection	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipme Wear safety glasses with side shields Butyl rubber or Viton® gloves are rece the glove supplier. Be aware that the	haust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender we not been established, maintain airborne levels to an ation and safety shower. ent (or goggles). Chemical goggles are recommended. ommended. Other suitable gloves can be recommended by liquid may penetrate the gloves. Frequent change is
propriate engineering ntrols lividual protection measure Eye/face protection Skin protection Hand protection	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipme Wear safety glasses with side shields Butyl rubber or Viton® gloves are reco the glove supplier. Be aware that the advisable. Wear appropriate chemical resistant of If engineering controls do not maintain	haust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender we not been established, maintain airborne levels to an ation and safety shower. ent of (or goggles). Chemical goggles are recommended. ommended. Other suitable gloves can be recommended by liquid may penetrate the gloves. Frequent change is clothing. n airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not
propriate engineering ntrols lividual protection measure Eye/face protection Skin protection Hand protection Other	Explosion-proof general and local exh Ventilation rates should be matched to exhaust ventilation, or other engineeri exposure limits. If exposure limits hav acceptable level. Provide eyewash sta s, such as personal protective equipme Wear safety glasses with side shields Butyl rubber or Viton® gloves are reco the glove supplier. Be aware that the advisable. Wear appropriate chemical resistant of If engineering controls do not maintain limits (where applicable) or to an acce	haust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ing controls to maintain airborne levels below recommender we not been established, maintain airborne levels to an ation and safety shower. ent o (or goggles). Chemical goggles are recommended. ommended. Other suitable gloves can be recommended by liquid may penetrate the gloves. Frequent change is clothing. n airborne concentrations below recommended exposure eptable level (in countries where exposure limits have not rator must be worn.

9. Physical and chemical properties

3. Filysical and chemical p	noperties
Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Clear liquid; invisible vapour.
Odour	Alcoholic.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	78.3 - 80 °C (172.94 - 176 °F)
Flash point	13 °C (55.4 °F) Closed cup
Evaporation rate	Expected to be rapid
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	3.3 % v/v (for Ethanol)
Explosive limit – upper (%)	19 % v/v (for Ethanol)
Vapour pressure	44.6 mm Hg (20 °C (68 °F) (for Ethanol))
Vapour density	1.4 - 1.6 (air=1.0)
Relative density	0.796 - 0.881 g/ml (25 °C (77 °F))
Solubility(ies)	
Solubility (water)	Complete
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	363 °C (685.4 °F) Ethanol
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion
Information on likely routes of e	
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the
physical, chemical and
toxicological characteristicsHeadache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and
blurred vision. Coughing.

Information on toxicological effects

Information on toxicological eff	ects		
Acute toxicity	Not expected to be acutely	toxic.	
Components	Species	Test Results	
Ethanol (CAS 64-17-5)			
Acute			
Inhalation			
Vapour			
LC50	Rat	117 - 125 mg/l, 4 Hours	
Oral			
LD50	Rat	10470 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitisatio	n		
Respiratory sensitisation	Not a respiratory sensitise	r.	
Skin sensitisation	This product is not expected to cause skin sensitisation.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity			
ACGIH Carcinogens			
Ethanol (CAS 64-17-5)	A3 Confirmed animal carcinogen with unknown relevance to humans.		
Canada - Manitoba OELs: c	arcinogenicity		
Ethanol (CAS 64-17-5)		Confirmed animal carcinogen with unknown relevance to humans	
Reproductive toxicity	This product is not expecte	d to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may b	be harmful.	

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Ethanol (CAS 64-17-5))		
Aquatic			
Acute			
Algae	EC10	Freshwater algae	11.5 mg/l, 72 hours
	EC50	Freshwater algae	275 mg/l, 72 hours
		Marine water algae	1900 mg/l
Fish	LC50	Freshwater fish	11200 mg/l, 24 hours
Invertebrate	EC50	Freshwater invertebrate	5012 mg/l, 48 hours
		Marine water invertebrate	857 mg/l, 48 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
Chronic			
Algae	NOEC	Marine water algae	1580 mg/l
Fish	NOEC	Freshwater fish	250 mg/l
Invertebrate	NOEC	Freshwater invertebrate	9.6 mg/l, 10 days
		Marine water invertebrate	79 mg/l, 96 hours

Components		Species	Test Results	
Other	NOEC	Lemna minor	280 mg/l, 7 days	
Other				
Acute				
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours	
Terrestrial				
Acute				
Plant	EC50	Terrestrial plant	633 mg/kg dw	
Persistence and degradability	Expected	to be readily biodegradable.		
Bioaccumulative potential	The produ	The product is not expected to bioaccumulate.		
Mobility in soil	Expected	Expected to be mobile in soil.		
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.			
13. Disposal consideratio	ons			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	The waste disposal c	5	ussion between the user, the producer and the waste	
Waste from residues / unused products	product re		ons. Empty containers or liners may retain some ainer must be disposed of in a safe manner (see:	

Contaminated packagingDisposal instructions).Contaminated packagingSince emptied containers may retain product residue, follow label warnings even after container is
emptied. Empty containers should be taken to an approved waste handling site for recycling or
disposal.

14. Transport information

TDG	
UN number	UN1987
UN proper shipping name	ALCOHOLS, N.O.S. (Ethanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	ll
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
ΙΑΤΑ	
UN number	UN1987
UN proper shipping name	Alcohols, n.o.s. (Ethanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	•
Packing group	I
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1987
UN proper shipping name	ALCOHOLS, N.O.S. (Ethanol)
Transport hazard class(es)	
Class	3
Subsidiary risk	
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
· ·	

15. Regulatory information

Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.	
Controlled Drugs and Subst	ances Act	
Not regulated.		
Export Control List (CEPA 1	999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed. Precursor Control Regulatio	ne	
Not regulated.	115	
nternational regulations		
•		
Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable. Kyoto Protocol		
Not applicable. Montreal Protocol		
Not applicable.		
Basel Convention		
Not applicable.		
nternational Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
Taiwaii		100

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	30-August-2021
Revision date	-
Version No.	01

This product is subject to YellowBee Packaging and Supplies Inc.'s terms and conditions. The information in this SDS is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the material and not as a guarantee of the properties thereof. No warranty guarantee or representation is made to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy itself as to the suitability of such information for its own particular use. This information relates only to the specific product designated and may not be valid for such product used in combination with any other materials or in any process. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations applicable to the use, storage, or handling of the product. THE COMPANY MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR USAGE OF TRADE, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Given the variety of factors that can affect the use and application of the product, which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to independently determine whether it is fit for a particular purpose, suitable, safe, and/or lawful for user's method of use or application.