PRODUCT DESCRIPTION:

The linear high bay is the lighting solution for a wide variety of applications and mounting heights. A choice of lumen outputs and color temperatures make the high efficacy the ideal solution for industrial, commercial and other high bay application.

LED Linear High Bay Spec

LOD-LHB4FT160W-40K

LOD-LHB4FT160W-50K

FEATURES:

- PMMA material
- Samsung 2835 LED chips
- Steel and aluminum body
- High quality LED chips with 100,000 hours
- 0-10V dimming available



DIMENSIONS:

Page: 1 of 2

SPECIFICATIONS:

| SPECIFICATION | Details | |
|-----------------------|---------------------------|--------------------|
| Model | LOD-LHB4FT160W-40K | LOD-LHB4FT160W-50K |
| Input Wattage (W) | 160W | |
| Lumens Delivered (LM) | 21,744LM | 21,792LM |
| Efficacy (LM/W) | 135.9LM/W | 136.2LM/W |
| CRI | 80 | 80 |
| Lifespan | 100,000 hours | |
| Color Temperature | 4,000K | 5,000К |
| Wattage Equivalent | 400W | |
| Dimmable | Yes | |
| IP Rating | IP54 | |
| Beam Angle | 120 | |
| Input Voltage | AC120-277V | |
| Power Factor | 0.9 | 0.9 |
| Housing | Steel & Aluminum | |
| Lens | Frosted | |
| Mounting | Hanging Chain | |
| Weight (LBS) | 18.25lbs | |
| THD | 20% | 20% |
| Size (inches) | 47.25" x 12.625" x 3.625" | |
| Certification | DLC, UL | |
| Operating Temperature | -20℃-40℃ | |
| Environment | Indoor | |
| Warranty | 5 years limited | |

4000K is a special-order request

•

