

CALL: 855-533-2288

OR SHOP ONLINE:

www.jubileeled.com Email: info@jubileeled.com

Wall Pack LED 13W Spec

SPECIFICATIONS:

SPECIFICATIONS:	
WATTAGE:	13W
MODEL #:	WP-13W-5K-JLL
ENERGY STAR #:	9530E-BK5
CERTIFICATIONS:	UL Energy Star, cETLus, FCC
VOLTAGE:	AC120277V
POWER FACTOR:	>0.95
FREQUENCY:	50/60 Hz
LUMENS:	800
LUMENS EFFICIENCY:	61.5 LM/W
KELVIN (CCT):	5000
THD:	<15%
CRI:	>84
IP RATING:	IP54
BEAM ANGLE (DEGREE):	90° Degrees
BASE TYPE / CONNECTION:	Wired
LENS:	Frosted
MATERIALS:	Dioxide Casting
POWER:	In-built driver
LED CHIPS:	smd 3030
LIFE SPAN (HOURS):	35,000 Hours
DIMMING COMPATIBLE:	No
LENGTH OF WARRANTY (YEARS):	5 Years Standard
PRODUCT SIZE:	8.5"x5.5"x3"
WEIGHT:	3 lbs
MOUNTING:	Wall Surface
WORKING ENVIRONMENT:	20°C to 50°C (4°F to 122°F)
SUGGESTED REPLACEMENT FOR:	60-90 Watt
POWER EFFICIENCY:	>90%



*** Note: Specifications are based on DLC's website. Actual product may have slight variations in tolerance range.

Features:

Heavy duty die-cast aluminum housing, fully sealed to be dirt and bug proof. High quality shatterproof glass refractor. Internal secondary heat sink to optimize thermal transfer and maximize performance and life of LED. Driver is mounted in direct contact with the casting for a low operating temperature and long life. Easy low cost maintenance and repair. UL, CUL, certified to wet location, DCL Listed.

Applications:

Industrial and commercial applications. For road and area lighting like: parking decks, auto dealerships, apartments, residential complexes, shopping malls, sporting complexes and fields, educational facilities, streets, roadways, parks, recreational bike paths, and municipal lot walls. 020815









