



**CALL: 855-533-2288**

OR SHOP ONLINE:

[www.jubileeled.com](http://www.jubileeled.com)

Email: [info@jubileeled.com](mailto:info@jubileeled.com)

## Wall Pack LED 40W Spec

### SPECIFICATIONS:

WATTAGE:	40W
WATTAGE OUTPUT:	43.06W
MODEL #:	WP-40W-5K-JLL
DLC #:	LOD--WP--40WSA
UL & CUL:	cETLus
CERTIFICATIONS:	cETLus, FCC,DLC
VOLTAGE:	AC120--277V
POWER FACTOR:	>0.95
FREQUENCY:	50/60 Hz
LUMENS :	3,098.76
LUMENS EFFICIENCY:	71.96lm/W
KELVIN (CCT):	5498
THD:	<15%
CRI:	86.2
IP RATING:	IP65
BEAM ANGLE (DEGREE):	95° Degrees
BASE TYPE / CONNECTION:	Wired
LENS:	Frosted/Clear
MATERIALS:	Aluminum Alloy + Borosilicate Glass
POWER:	External
LED CHIPS:	smd 3030
LIFE SPAN (HOURS):	50,000 Hours
DIMMING COMPATIBLE:	No
LENGTH OF WARRANTY (YEARS):	5 Years Standard
PRODUCT SIZE:	363 x 231 x 188mm
WEIGHT:	3.81KG/8.38lbs
MOUNTING:	Wall Surface
WORKING ENVIRONMENT:	-20°C to 50°C (-4°F to 122°F)
SUGGESTED REPLACEMENT FOR:	175 Watt
POWER EFFICIENCY:	>90%
PERCENTAGE OF WATTAGE SAVED:	>70%



\*\*\* Note: Specifications are based on DLC's website. Actual product may have slight variations in tolerance range.

### Features:

Heavy duty die-cast aluminum housing, fully sealed to be dirt and bug proof. High quality tempered glass optics. Integral secondary heat sink to optimize thermal transfer and maximize performance and life of LED. Driver is mounted in direct contact with the casting for low operating temperature and long life. Polyester powder-coated finish, rust and corrosion proof; stabilized to extreme climate changes without cracking or peeling.

### Applications:

Industrial and commercial applications. For road and area lighting like: parking decks, auto dealerships, high masts, apartments, residential complexes, shopping malls, sporting complexes and fields, educational facilities, streets, roadways, parks, recreational bike paths, and municipal lots. 020815

