

In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 4 Hour Max, Without Hold, Ivory

Item FD4H



PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 4-Hour
- ▶ SPST (Single-Pole Single-Throw)
- ▶ Breaks circuit at end of timing cycle
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single- or multi-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ No neutral connection is required
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General

| | |
|--------------------------------|---|
| Model Number | FD4H |
| Description | Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 4 Hour Max, Without Hold, Ivory |
| UPC Code | 078275074019 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | TUNISIA |
| Warranty Period | 1-Year limited |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |
| Harmonized Code | 9107.00.8000 |

Control Specifications

| | |
|--------------------|-------------------|
| Operation Mode | Countdown |
| Countdown Time | 4 hrs |
| Hold Mode Included | No |
| Mechanism Type | Analog/Mechanical |

Mechanical Specifications

| | |
|---------------------------|-------------------------|
| Wall Plate Configurations | Single-Gang; Multi-Gang |
|---------------------------|-------------------------|

Dimensions

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.25 in

Material Specifications

Color Ivory

Load Ratings

Resistive Heater 20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC

Tungsten (Incandescent) Range(s) 7 A, 125 VAC, 50/60 Hz, 875 W

Motor Load Ratings Ranges 1 HP, 125 VAC; 2 HP, 250 VAC

Electrical Specifications

Input Voltage Range(s) 125-277 VAC, 50/60 Hz

Wiring Configurations Single

Switch Type SPST

Neutral Connection Required No

Environmental Specifications

Temperature (operation) 40 - 120 °F / 4 - 49 °C

Packaging

Shipping Weight (lbs) 0.299

Unit Carton Dimensions (H x W x D) in 4.63 x 2.13 x 2.88 in

Standards and Certifications

CSA Certification cCSAus

Other Certifications and Compatibilities RU

California Proposition 65 DEHP

PDF Standards And Certifications cCSAus; RU

Epi Certifications cCSAus; RU

ACCESSORIES



146MT573
Knob-Wall Switch FD Series - Ivory



146MT574
Knob-Wall Switch FD Series - White



146MT575
Knob-Wall Switch FD Series - Almond



148FD5076
Plate for 4-Hr without HOLD, Ivory (FD34H, FD4H)