

# Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 208-277 V

## Item K4253



#### **PRODUCT DESCRIPTION**

These photocontrols are provided with a swivel arm for easy and flexible installation to standard outdoor light fixtures or electrical boxes.

### **FEATURES**

- ► Mechanical bimetal switch with Cadmium Sulfide photocell
- Delay feature prevents unwanted OFF switching
- ► High strength, UV resistant plastic housing
- ► Swivel with 1/2"-14 NPSM threaded stem
- ► Washer gasket and locking nut included
- ▶ #18 AWG, 6" wire leads

## **APPLICATIONS**

Outdoor Lighting Control

### **TECHNICAL DATA**

**SP** 

K4253
Stem and Swivel Mount Thermal Photocontrol, 208-277 V
078275067769
Intermatic
CHINA
1-Year limited
Outdoor
Thermal
5
3650
HID; Fluorescent; Incandescent
Stem and Swivel Mount
Тор
30 sec to 90 sec
Cadmium Sulfide
Mechanical Bimetal
ON
1 to 5 fc
3 to 15 fc
4
101.6
1 3/8 34.9



Product Depth (in)	1 3/8
Product Depth (mm)	34.9
Wire Lead Length (in)	6
Wire Lead Length (mm)	152
Wire Size Max	#18 AWG
Material Specifications	
Cover Color	Gray
Housing Material	Polycarbonate
Load Ratings	
Magnetic Ballast Range(s)	8.3 A, 1700-2300 VA
Tungsten Range(s)	15 A, 3100-4150 W
Electrical Specifications	
Wiring Option	Wire leads
Input Voltage Range(s)	208-277 VAC, 50/60 Hz
Packaging	
Shipping Weight (lbs)	0.1
Unit Carton Dimensions (H x W x D) in	4.88 x 1.75 x 3 in
Environmental Specifications	
Temperature (operation)	-40°C60°C
Standards and Certifications	
CSA Certification	CSA
Other Certifications and Compatibilities	Title 20
California Proposition 65	DEHP
PDF Standards And Certifications	CSA; Title 20
Epi Certifications	CSA; Title 20



## ACCESSORIES



22LG116 Light Guard Accessory for K4100 Series, K4200 Series Thermal Photocontrols



K42-SW-A Swivel Arm Accessory for EK4136S, K4100 Series Stem Mount Photocontrols



6LV1352 Light Shield Accessory for EK4036S, EK4436SM, K4000 Series Button Photocontrols