

Occupancy Sensor - Commercial Grade In-Wall PIR Occupancy/Vacancy Sensor, White

Item IOS-DOV-WH



PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. The sensor switch can turn a load ON and hold it as long as the sensor detects occupancy. After no motion is detected for the set time delay, the load turns OFF automatically. The sensor switch has one relay (equal to single pole switch), it also includes Ambient Light Level Sensor.

FEATURES

- ▶ Passive Infrared (PIR) sensing for presence detection
- ▶ Coverage: 180°, 1200 ft2 with non-obstructed views
- ▶ User-selectable Vacancy or Occupancy switch mode
- ▶ Zero-crossing technology for long life and performance
- ▶ Adjustable ambient light sensor override
- ▶ Incandescent/Fluorescent/CFL compatible
- ▶ IOS-DOV models require a neutral connection
- ▶ Fits standard decorator wall plate (included)
- ▶ Adjustable Sensitivity Settings: (30% - 100%)
- ▶ Automatic ON/OFF Control
- ▶ Push button ON/OFF

APPLICATIONS

- ▶ Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-DOV-WH
Description	Commercial Grade In-Wall PIR Occupancy/Vacancy Sensor, White
UPC Code	078275125209
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	CHINA
Application Compatibilities	Incandescent; Fluorescent; CFL
Market	Commercial; Industrial; Residential; Utility

Control Specifications	
Sensor Switch Type	Occupancy; Vacancy
Sensor Technology	PIR (Passive Infrared); Zero-crossing
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	30 lux
Adjustable Light Level Max	Daylight
PIR Coverage Area (sq ft)	1200

Mechanical Specifications	
Mount Type	In-Wall
PIR Coverage Pattern (degrees)	180
Maximum Mounting Height (ft)	4 ft

Dimensions	
Product Height (in)	2.625
Product Height (mm)	67
Product Width (in)	1 5/16
Product Width (mm)	33
Product Depth (in)	1.75
Product Depth (mm)	44

Material Specifications	
Color	White
Includes Wall Plate	Yes

Load Ratings	
Resistive Heater	12 A
Inductive Load Ratings Ranges	800 VA
Motor Load Ratings Ranges	1/4 HP
Ballast Fluorescent Ranges	800 VA
Tungsten (Incandescent) Range(s)	800 W

Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Number of Circuits	1
Neutral Connection Required	Yes

Packaging	
Shipping Weight (lbs)	0.399
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	5 x 2.25 x 3 in

Environmental Specifications	
Temperature (operation)	32 - 131°F / 0 - 55°C

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	Title 20
California Proposition 65	None
Epi Certifications	Title 20; cULus