

In-Wall Timer - 7-Day Standard Programmable Timer, 120 VAC, 12A, White

Item EJ600



PRODUCT DESCRIPTION

A 12 A rated timer that provides full 7-day programming capabilities with dusk-to-dawn functionality, ideal for use with medium to low power loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Astronomic clock feature determines dawn and dusk times
- ▶ Automatic Daylight Saving Time (DST) adjustment
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single or 3-way switch compatible installation
- ▶ Incandescent/fluorescent compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	EJ600
Description	7-Day Standard Programmable Timer, 120 VAC, 12A, White
UPC Code	078275127876
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Application Compatibilities	Incandescent; Fluorescent
Harmonized Code	9107.00.8000

Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Operation Mode	24-hour
Operation Features	Astronomic; Daylight Saving Time
Mechanism Type	Digital/Electrical
Backup Type	Battery
Backup Protection Time	100 Hours
Battery Type	Rechargeable
Battery Service Type	Non-Serviceable

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.4375 in

Material Specifications

Color White
Includes Wall Plate No

Load Ratings

Resistive Heater 12 A, 1440 W
Tungsten (Incandescent) Range(s) 1800 W, single-gang; 1440 W, multi-gang
Ballast Fluorescent 4 A, 500 VA
Motor Load Ratings Ranges 1/2 HP
Inductive Load Ratings Ranges 500 VA, 120 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s) 120 VAC, 60 Hz
Wiring Configurations Single; 3-Way
Neutral Connection Required Yes

Environmental Specifications

Temperature (operation) 32 - 104 °F / 0 - 40 °C

Packaging

Shipping Weight (lbs) 0.293
Unit Carton Dimensions (H x W x D) in 6.13 x 2.13 x 3 in

Standards and Certifications

CSA Certification cCSAus
California Proposition 65 DEHP
PDF Standards And Certifications cCSAus
Epi Certifications cCSAus