

Electronic Timer Control - 24-Hour/365 Day 2-Circuit Electronic Control, 120-277 VAC, 2-SPST/DPST, Indoor Metal Enclosure

Item ET2125C



PRODUCT DESCRIPTION

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application.

FEATURES

- ▶ 100-hour supercapacitor eliminates the need for batteries
- ▶ Up to 96 set points or events
- ▶ Up to 50 holiday blocks with schedule capabilities
- ▶ Automatic input voltage selection from 120 to 277 VAC
- ▶ Additional mode of operation turns the ON/OFF buttons into 2-hour overrides
- ▶ Configurable outputs allow the control of various voltages and applications
- ▶ Relays incorporate zero-crossing technology to extend the life of the control
- ▶ Non-volatile EEPROM memory protects programming indefinitely
- ▶ LED compatible
- ▶ USB port makes transferring and saving of schedules easy
- ▶ 2-year limited warranty

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

TECHNICAL DATA

| General | |
|--------------------------------|--|
| Model Number | ET2125C |
| Description | 24-Hour/365 Day 2-Circuit Electronic Control, 120-277 VAC, 2-SPST/DPST, Indoor Metal Enclosure |
| UPC Code | 078275148017 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 2-Year limited |
| Application Compatibilities | LED |
| Control Specifications | |
| Minimum ON/OFF Times | 1 min |
| Minimum Pulse Time | 2 sec |
| Maximum Pulse Time | 2 sec |
| Maximum ON/OFF Times | Indefinite |
| Maximum ON/OFF Operations | 96 |
| Setpoint Program Count | 96 |
| ON/OFF Operations | 96 |
| Operation Features | Holiday |
| Operation Mode | 24-hour |
| Daylight Savings Adjustment | Automatic |

| | |
|-------------------------|----------------|
| Backup Restoration Time | 30 Minutes |
| Backup Type | Supercapacitor |
| Backup Protection Time | 100 Hour |

Mechanical Specifications

| | |
|----------------|---------------------|
| Enclosure Type | Indoor type 1 metal |
|----------------|---------------------|

Dimensions

| | |
|-----------------------------------|-----------------------------|
| Product Dimensions (H x W x D) in | 7.875 x 5.125 x 3.4375 in |
| Wire Size Min | #14 AWG |
| Wire Size Max | #8 AWG |
| Knockout Dimensions Bottom | (2) combination 1/2" - 3/4" |
| Knockout Dimensions Back | (1) combination 1/2" - 3/4" |

Load Ratings

| | |
|---|---------------------------------|
| Magnetic Ballast (NO) Range(s) | 20 A, 120-277 VAC |
| Resistive (NO) Range(s) | 20 A, 28 VDC; 30 A, 120-240 VAC |
| Inductive Load Ratings NO Ranges | 30 A, 120-240 VAC |
| Electronic Ballast Load Ratings NO Ranges | 10 A, 120/277 VAC |
| Tungsten (NO) Range(s) | 5 A, 120-277 VAC |
| Motor Load Ratings NO Ranges | 1 HP, 120 VAC; 2 HP, 240 VAC |

Electrical Specifications

| | |
|-------------------------------|-------------------------|
| Voltage Selection Type | Auto Voltage |
| Wiring Option | Terminals |
| Input Voltage Range(s) | 120-277 VAC, 60 Hz |
| Number of Circuits | 2 |
| Switch Type | 2xSPST, 1xDPST or Pulse |
| Maximum Power Consumption (W) | 5 W |
| Electronic Series | ET2000 Series |

Packaging

| | |
|---------------------------------------|---------------------|
| Shipping Weight (lbs) | 2.75 |
| Unit Carton Dimensions (H x W x L) in | 8 x 3.15 x 5.236 in |

Environmental Specifications

| | |
|-------------------------|--------------------------------------|
| Temperature (operation) | -40 °F to 104 °F / (-40 °C to 40 °C) |
|-------------------------|--------------------------------------|

Standards and Certifications

| | |
|--|-------|
| UL Certification | cULus |
| Other Certifications and Compatibilities | LED |
| California Proposition 65 | Lead |

DRAWINGS AND DIAGRAMS

