

## **SPECIFICATION SHEET**

Type:

Model:

Project:

# MODEL 9206 Landscape Series • Path & Spread Lights

### **FIXTURE SPECIFICATIONS:**

**HOUSING:** 

Die-cast, copper-free aluminum

STEM:

½" schedule-40 aluminum pipe with ½" NPT.

FINISH:

Polyester powder-coat finish available in Black, Architectural Bronze, Dark Bronze, Granite, White, Architectural Brick, Light Bronze, Special Bronze, Glossy Grey, Rust, Hunter Green, Weathered Bronze, Weathered Iron, Graphite Metallic, Verde, Pewter, Mocha and Olde Finish.

SOCKET/LAMP HOLDER:

Top grade ceramic socket with nickel contacts, stainless steel springs, and Teflon-jacketed wire leads.

LENS:

Clear, prismatic, high-impact, polycarbonate spread lens.

LAMP TYPE:

T3 - 20W max. LN-10 T3 Halogen (10W) Standard.

MOUNTING:

Bottom of stem threaded with  $\frac{1}{2}$ " NPT. Fixture may be mounted into threaded hubs in junction boxes, ground stakes, or floor-mounting canopies.

#### **FASTENERS:**

All fasteners are stainless steel.

#### WIRING:


Prewired with a three-foot pigtail of 18-2 direct-burial cable and underground connectors for a secure connection to supply cable.


#### **CERTIFICATION:**

UL Listed to U.S. and Canadian safety standards for low voltage landscape luminaires (UL 1838). Maximum wattages allowed by Underwriters Laboratories (UL) for U.S. and Canadian markets may vary. Maximum wattages specified are Underwriters Laboratories U.S. standard. Please contact Vista for any questions about maximum wattages allowed by UL Canadian standards.

All Vista luminaires are MADE IN U.S.A.

### **DIMENSIONS:**







Vista Professional Outdoor Lighting reserves the right to modify the design and/or construction of the fixture shown without further notification.



# **SPECIFICATION SHEET**

# MODEL 9206 Landscape Series • Path & Spread Lights

## FIXTURE ORDERING INFORMATION

TO ORDER FIXTURE: Select appropriate choice from each column as in the following example.

EXAMPLE: PR-9206-B-10T3

Standard 10T3 - 10W  B - Black Z - Architectural Bronze 20W Maximum LN-10 T3 Halogen (10W GT - Granite W - White 2.5-W-T3  Premium LNT3-2.5-W-G-LED	W) Standard
Z - Architectural Bronze DZ - Dark Bronze GT - Granite W - White  Premium  13 Nalogen 20W Maximum LN-10 T3 Halogen (10V 2.5-W-T3 LNT3-2.5-W-G-LED	W) Standard
I I	
BR - Architectural Brick LZ - Light Bronze SB - Special Bronze GG - Glossy Gray R - Rust HG - Hunter Green WB - Weathered Bronze WI - Weathered Iron GM - Graphite Metallic  W-LB2ND - Warm 2.5W N-LB2ND - Neutral 2.5W C-LB2ND - Cool 5.5W  W-LB5ND - Warm 5W N-LB5ND - Neutral 5W C-LB5ND - Cool 5W	W
Hand Finished (Please see lamp order column on lamp guid	
G - Verde P - Pewter M - Mocha	
	BR - Architectural Brick LZ - Light Bronze SB - Special Bronze GG - Glossy Gray R - Rust HG - Hunter Green WB - Weathered Bronze WI - Weathered Iron GM - Graphite Metallic  Hand Finished  G - Verde P - Pewter  W-LB2ND - Warm 2.5V N-LB2ND - Neutral 2.5' C-LB2ND - Cool 2.5W  W-LB5ND - Warm 5W N-LB5ND - Neutral 5W C-LB5ND - Cool 5W  (Please see lamp order column on lamp guide product catalog.)

Fixtures shipped with standard lamp, unless otherwise specified. Fixtures shipped with specified mounting hardware.