

SPECIFICATION SHEET

• Directional Lights

1633 Staunton Ave Los Angeles, CA 90021 FAX. TEL. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

Cast Brass

PRODUCT #: CL-525B-GM

Fixture Specifications:


Housing & Shroud: Corrosion Resistant Cast Brass.

Finish: GM- Gun Metal. Natural toning process. GM finish will vary due to artistic process. AB & SI finishes also available.

Lens: Clear and heat resistant convex glass.

- Socket: Top grade loose ceramic bi-pin socket, with spring loaded design.
- Wiring: Fixture is prewired with a 3-ft 18-2 SPT2-W direct burial cord. Wire connector sold seperately. Universal connector (CX-839), silicone filled wire nut (CX-854) or quick locking wire connector (CX-LOC) are available from Corona Lighting.
- Lamp: 12V, MR-16, 50W max. Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Gasket:	Silicone double gasketed for water tight sealing
Knuckle:	Adjustable cast brass knuckle with thumb screw and $\frac{1}{2}$ " NPT threaded male hub on bottom.
Mounting Spike:	Standard injection molded spike with $\frac{1}{2}$ " NPT threaded female hub.
Electrical Notes:	A remote 12V transformer is required. Options are available from Corona Lighting. Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.
Warranty:	Limited lifetime warranty on fixture housing against manufacturer's defects.



LAMP NUMBER	WATTS	SPREAD	LUMEN	TEMP.	HOURS	EQUIVALENT	
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt	TYPE: DATE:
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt	DATE.
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt	JOB NAME & ADDRESS:
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt	
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt	BRODUCT #
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt	PRODUCT #:
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt	TOTAL QUANTITY:
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt	
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt	LAMP TYPE & WATTAGE:
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt	TRANSFORMER:
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt	
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt	CONTRACTOR:
Single color MR-16 LED avail	able in AME	BER, BLUE, GREEN	, PURPLE, RI	ED and VIOLET	-		SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below: • CL - product # - lamp - wattage - lamp angle Example: CL-525B-GM-L-ED16-5W-FL

CL - 525B-GM - L-ED16 - 5W -FL

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



ACCESSORIES SHEET

PRODUCT # : CL-525B-GM

Mounting Pedestals

1	
CX-603-VG	3" PVC Mounting Pedestal, ¹ ⁄ ₂ " NPT Female Brass Hub on top, Verde Green
CX-603-BK	3" PVC Mounting Pedestal, ¹ / ₂ " NPT Female Brass Hub on top, Black
CX-602-VG	2" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-602-BK	2" PVC Mounting Pedestal, ½" NPT, Black
CX-601-VG	1" PVC Mounting Pedestal, 1/2" NPT, Verde Green
CX-601-BK	1" PVC Mounting Pedestal, ½" NPT, Black



CX-603-BK

CX-621-BK	1" PVC Cap, ½" NPT, Black
CX-621-VG	1" PVC Cap, 1/2" NPT, Verde Green
CX-622-BK	2" PVC Cap, ½" NPT, Black
CX-622-VG	2" PVC Cap, 1/2" NPT, Verde Green
CX-624-BK	3" PVC Cap, ½" NPT Female Brass Hub, Black
CX-624-VG	3" PVC Cap, ½" NPT Female Brass Hub, Verde Green

Mounting Canopies

CX-705B-GM	Brass Flat Canopy, ½ NPT, Gun Metal
CX-709B-GM	Brass Raised Canopy, ½ NPT, Gun Metal
CX-718B-GM	5" Brass Canopy, 3-Hole ½ NPT, Gun Metal
CX-719B-GM	Brass Tree Mounting Bracket, 1/2" NPT, Gun Metal
CX-720-BR	Brass Tree mount Canopy with 9" Rubber Strap stretches to 14, Natural Brass
CX-721-BR	Brass Tree mount Canopy with 15" Rubber Strap stretches to 22", Natural Brass
CX-722-BR	Brass Tree mount Canopy with 22" Rubber Strap stretches to 33", Natural Brass
CX-723-BR	Brass Tree mount Canopy with 31" Rubber Strap stretches to 45", Natural Brass
CX-724-BR	Brass Tree mount Canopy with 41" Rubber Strap stretches to 61", Natural Brass
11/2	





 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

Directional Lights

Cast Brass

Ground Spikes

CX-642-BK	8.5" ABS Spike, ½" NPT, Black
CX-642-BZ	8.5" ABS Spike, 1/2" NPT, Bronze
CX-643-BZ	8.5" ABS Spike, 1/2" NPT, Bronze



CX-647-BK

CX-646-BK	8" ABS Spike, ½" NPT, Black
CX-646-BR	8" ABS Spike, ½" NPT, Natural Brass
CX-646-SS	8" ABS Spike, 1/2" NPT, Stainless Steel
CX-647-BK	10.5" Heavy Duty ABS Spike, ½" NPT, Black

Mounting Risers

CX-682B-GM	6" Brass Riser, ½ NPT Male/Female, Gun Metal
CX-683B-GM	12" Brass Riser, $\frac{1}{2}$ NPT Male/Female, Gun Metal
CX-684B-GM	18" Brass Riser, ½ NPT Male/Female, Gun Metal
CX-685B-GM	24" Brass Riser, ½ NPT Male/Female, Gun Metal



CX-718B-GM



ACCESSORIES SHEET

PRODUCT # : CL-525B-GM

Mounting Posts For Sign Light & Path Light Applications

CX-678B-GM	24" Brass Single Head Post, Gun Metal
CX-679B-GM	24" Brass Double Head Post, Gun Metal
CX-690B-GM	18" Brass Single Head Post, Gun Metal
CX-693B-GM	18" Brass Double Head Post, Gun Metal

•CX-718B-GM (Mounting Canopies pg 2) is required for sign light installation.



1633 Staunton Ave Los Angeles, CA 90021 TEL. FAX. (800) 727-9262 (800) 727-9957 (213) 747-4500 (213) 747-3234

E-Mail: sales@coronalighting.com


Directional Lights

Cast Brass

Cable Connectors

CX-854	Direct Burial Silicone Filled Wire Nut, Tan

- CX-858 Speedy Cable Connector, Supply Cable up to 10-2, **Black**
- CX-839 Universal cable connector, Supply cable up to 8-2, one/Pack Black
- CX-LOC Quick-Locking Silicone Filled Wire Connector, 25 Sets (50 per Pack)



|-−⁵⁄₈"-->|

Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

• For MR-16 Lenses and Louvers, you will need the CX-238

