

## **SPECIFICATION SHEET**

 1633 Staunton Ave

 Los Angeles, CA
 90021

 TEL.
 FAX.

 (800) 727-9262
 (800) 727-9957

 (213) 747-4500
 (213) 747-3234

E-Mail: sales@coronalighting.com

PROD	UCT # : C	L-649	3-AB		•Area	Lights	• Cast Brass	
Fixture	Specificatio	ns:						
Housing:	Brass shade, adjusta	able in heigh	t for light c	ontrol.	Wiring	:	Fixture is prewired with a 3ft, 18-2 direct burial c	
Stem:	· •	Solid brass pipe with ½" NPT on bottom.				Wire connector sold seperately. Universal connect		
							( <b>CX-839</b> ) or silicone filled wire nut ( <b>CX-854</b> ) is available from Corona Lighting.	
Finish:	AB finish will vary du	<b>B- Antique Bronze</b> . Natural toning process. B finish will vary due to artistic process. so available in <b>GM- Gun Metal</b>				ing Spike:	Standard injection molded spike with ½" NPT threaded female hub.	
Lens:	-	Clear glass, cover over lamp providing sprinkler vater protection. Frosted lens ( <b>CX-308-FR</b> ) available.				Electrical Notes:	A remote 12V transformer is required. Options are available from Corona Lighting.	
Socket:	S.C. Bayonet socket	S.C. Bayonet socket, easy tool free lamp access.					Voltage range for 12V halogen lamps are 11V-12.5	
Lamp:	standard. LED lamp 2700K-warm white o	volt, S.C Bayonet 27W Max. L-SCB-1141 (18W) andard. LED lamps available in 2W and 2.5W, with 00K-warm white or 3000K-cool white color nperature. Xenon and halogen lamps also available. <b>Warranty:</b>					Voltage range for LED lamps are 8V-21V. Proper grease/lubricant is suggested on threaded parts during installation process. Limited lifetime warranty on fixture housing and	
Gasket:	Silicone "O" ring gasket seals lens to socket housing for water tight sealing.						stem against manufacturer's defects.	
18" St	49B-AB tandard a shown	- 81 -		2'3"   2W	<b>E D</b> and 2.5	CL-649E 12" Sten		
VAILABLI	E LED LAMPS (Coro	na LED lamps ha	ave a five (5) y	ear limited warr	anty against man	ufacturer's defects		
AMP NUMBE	R WATTS	BE/ SPREAD	AM LUMEN	_ COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALEN	r	
-EDBA-2W	2	360°	200	2700K	25,000	20 Watt	TYPE: DATE:	
EDBA-2.5V		180°	240	2700K	25,000	35 Watt 20 Watt	JOB NAME & ADDRESS:	
-EDBA-2W-3 -EDBA-2.5W		360° 180°	210 250	3000K 3000K	25,000 25,000	35 Watt		
-EDBA-AM*		360°	170	2000K	25,000	20 Watt	-   -   PRODUCT #:	
	E HALOGEN LAM		BEAM		COLOR &	RATED		
		SPRE	AD		TEMP.	HOURS	TOTAL QUANTITY:	
-SCB-89 -SCB-93	7 13			75 190	2700K 2700K	750 700	LAMP TYPE & WATTAGE:	
-SCB-1141 -SCB-1156	18 27			265 400	2700K 2700K	1,500 1,200	TRANSFORMER:	
				400	21001	1,200		
AM- Amber colo	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,							

CL - 649B-AB - L-EDBA - 2W-3K

• Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.