UNIQUE LIGHTING SYSTEMS®

CANTERBURY: 12V & 24V Copper Area Light

PROJECT:	
TYPE:	
CATALOG NUMBER:	
LAMP(S):	
NOTES:	

FIXTURE ORDERING INFORMATION

VOLTAGE

12=12 Volt

24=24 Volt

Example: CANT-12-L2 (Solaris, 12 Volt, 2 Watt, 3000K LED T3, 25' Wire Lead, Natural Copper)

MODEL NAME CANT

WATTAGE L1= LED, 1W, 3000K L2= LED, 2W, 3000K 20= 20W Halogen NL= No Lamp

Standard Finish Natural Copper

applies to all powde products. Custom of available upon request. to all powder . Custom co

Stock powder coated colors displayed are subject to varying lead-times and will incur an additional cost. A Limited Warranty

inquire about cost and lead times. Contact factory for custom colors and matching paint oprions.

WIRE LENGTH

Leave blank for standard 25' length * 0=3' wire lead * 50= 50' wire lead

FINISH

leave blank for standard NC finish P= Standard powder coat finishes. List your desired color in the order comments area.

OPTIONS

* 6P= Six Pack

NOTE: Pre-lamped LED fixtures are NOT available with 24V lamps. LED fixtures are available ONLY with a 25' wire lead. For additional painted finishes or six pack options contact our factory.

Powder Coated Finishes

Tucson Tan	TT
White	WH
Black	ВК
Verde Green	VG
Titanium Knight	ТК

FLEXTM Unique Lighting Systems® fixtures are available with LED lamps. Series LED Place specify the lamp code when ordering.

SPECIFICATIONS

Our Commitment

Unique Lighting Systems' highest commitment is to set the standard for manufacturing innovative and quality products. This commitment is evident through our detailed inspection processes and extensive field testing. From the initial design process of each product, to the final assembly of each custom-made individual part, our manufacturing process accomplishes the highest level of performance and durability carried through to final delivery to the end user. Durable construction and beautiful styling make Unique fixtures the ideal solution for any residential or commercial application. Unique Lighting[™] already holds numerous product patents and we are constantly developing innovative ideas to help expand the lighting industry.

Materials

Crafted from extruded copper.

Stem

Copper unibody design provides enclosed, water resistant wireway. Integrated bung for maximum mechanical strength. The Orbital Lock Nut™ allows for locking the horizontal rotation without adjusting the stake.

Collar

Machined brass, fully articulating.

* Only available with the NL wattage option

NC

der coated colors are st. Please

Shroud Fully machined copper. Reflective Powder Coat Interior.

Unique Lighting Systems® reserves the right to modify the design and/or construction of the fixture shown without further notification.

Lens

Shock resistant, frosted polycarbonate globe lens.

Lamp

For use with a halogen lamp up to 20W. FLEX™ Series LED lamps are available in 1W or 2W T3 lamps. LED lamps are available in 3000K color temperatures

Electrical Requirements

A remote 12V or 24V transformer required, may be ordered separately from Unique Lighting Systems®. Voltage range for 12V halogen lamps is 10.8V to 12V. Voltage range for 24V halogen lamps is 21.6V to 24V. Voltage range for 12V FLEX[™] Series LED lamps is 10V-18V.

Socket

Specification grade, beryllium copper lamp holder. GU5.3 base.

Wiring

Exclusive UF Intelli-Flex wire with anti-moisture migration connections.

Mounting Stake

Standard mounting stake is injection molded PVC with a 1/2" NPS threaded female fitting.

Finish

Natural Copper finish is standard. Unique™ Lightings' Natural Copper finish is a "living finish" and will naturally patina and change over time. Polyester powder coat finishes are also available (see chart above).


Warranty

The Copper Knights Family of products from Unique Lighting Systems® carries a limited 15 year warranty against manufacturer's defects.

Manufacturing

Manufactured to ISO 9001-2008 Quality standard.





5825 Jasmine Street Riverside, CA 92504 T 800-955-4831 F 800-955-9852



