

# UNIQUE LIGHTING SYSTEMS®

**Tiki Light**  
Post Mounted Tiki Light  
Signature™ Series



## ISLANDER: 12V & 24V Brass/Copper Tiki Light

PROJECT:	
TYPE:	
CATALOG NUMBER:	
LAMP(S):	
NOTES:	


## FIXTURE ORDERING INFORMATION

Example: IB-12-L1 (Islander, Brass, 12 Volt, 1 Watt, 3000K LED T3, 25' Wire Lead, Weathered Brass)

MODEL NAME	VOLTAGE	WATTAGE	WIRE LENGTH	FINISH	OPTIONS
IB = Brass	12=12 Volt	L1= LED, 1W, 3000K	Leave blank for standard 25' length	leave blank for standard WB or NC finish	
IC = Copper	24=24 Volt	L2= LED, 2W, 3000K	* 0= 3' wire lead	P= Standard powder coat finishes.	List your desired color in the order comments area.
		35= 35W Xelogen	* 50= 50' wire lead		
		NL= No Lamp			

**NOTE:** Pre-lamped LED fixtures are NOT available with 24V lamps. LED fixtures are available ONLY with a 25' wire lead. For additional painted finishes contact our factory.

## DIMENSIONS:



### Powder Coated Finishes

Tucson Tan	TT
White	WH
Black	BK
Verde Green	VG
Titanium Knight	TK

### Standard Finish

Weathered Brass	WB
-----------------	----

\*Stock powder coated colors displayed are subject to varying lead-times and will incur an additional cost. A Limited Warranty applies to all powder coated products. Custom colors are available upon request. Please inquire about cost and lead times. Contact factory for custom colors and matching paint options.

**FLEX™** Unique Lighting Systems® fixtures are available with LED lamps. Please specify the lamp code when ordering.

\* Only available with the NL wattage option.

Unique Lighting Systems® reserves the right to modify the design and/or construction of the fixture shown without further notification.

## SPECIFICATIONS

### Our Commitment

Unique Lighting Systems' highest commitment is to set the standard for manufacturing innovative and quality products. This commitment is evident through our detailed inspection processes and extensive field testing. From the initial design process of each product, to the final assembly of each custom-made individual part, our manufacturing process accomplishes the highest level of performance and durability carried through to final delivery to the end user. Durable construction and beautiful styling make Unique fixtures the ideal solution for any residential or commercial application. Unique Lighting™ already holds numerous product patents and we are constantly developing innovative ideas to help expand the lighting industry.

### Materials

Crafted from extruded brass or copper.

### Stem

Brass or copper unibody design provides enclosed, water resistant wireway. Integrated bung for maximum mechanical strength. High temperature, double o-ring retention collar provides weather-tight seal.

### Collar

Machined brass, threaded.

### Shroud

Fully machined. Reflective Powder Coat Interior.

### Snuff Cap & Chain

Brass cap and chain.

### Lamp

For use with a xelogen lamp up to 35W. **FLEX™** Series LED lamps are available in 1W or 2W T3 lamps. LED lamps are available in 3000K color temperatures.

### Electrical Requirements

A remote 12V or 24V transformer required, may be ordered separately from Unique Lighting Systems®. Voltage range for 12V halogen lamps is 10.8V to 12V. Voltage range for 24V halogen lamps is 21.6V to 24V. Voltage range for 12V **FLEX™** Series LED lamps is 10V-18V.

### Socket

Specification grade, beryllium copper lamp holder. GU5.3 base.

### Wiring

Exclusive UF Intelli-Flex wire with anti-moisture migration connections.

### Mounting Stake

Injection molded ABS perma post with a ½" NPS threaded female fitting.

### Finish

Exclusive Weathered Brass or Natural Copper finish is standard. Unique™ Lightings' Weathered Brass and Natural Copper finishes are a "living finish" and will naturally patina and change over time. Polyester powder coat finishes are also available (see chart above).

### Warranty

The Signature Series Family of products from Unique Lighting Systems® carries a limited lifetime warranty against manufacturer's defects.

### Manufacturing

Manufactured to ISO 9001-2008 Quality standard.



UL 2108:2004 R12.07  
CSA C22.2.9.0-96 (R2006)