



WARNING

Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool.

NFPA® RATINGS

Health: 1; Flammability: 2; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; 2-propanol/67-63-0; Quaternary ammonium compounds/68308-67-8



RESILIENT FLOOR CARE

ANTI-STATIC SPRAY

Removes Static Electricity
From Carpets, Floors,
Upholstery, Work Surfaces,
CPT Screens and
Computer Equipment

• LONG LASTING

DESCRIPTION

This professional strength anti-static spray protects valuable data, eliminates memory loss, and other annoying computing errors caused by static electrical charge. It provides long lasting residual protection for reduced downtime and fewer glitches, and helps to reduce attraction of dust to CRT screens. Designed for use in offices, static sensitive computer areas, word processing and other electronic environments. This non-staining formula is made to be used on fabrics and hard surfaces found on and around computers.

DIRECTIONS

Carpet and Fabrics: Mist lightly but thoroughly over exposed surfaces. Do not soak. Allow to dry before using. Test material for water spotting before use. Treat casters and frames on rolling furniture.

Hard Floors: Dilute 1:5 with water and damp mop entire floor including access areas and lanes.

Hard Surfaces: Dampen a clean, lint-free cloth, wiping lightly over computer cabinets, CRT screens, rollers, chutes, guides and trays of printers, bursters, decollators, sorters and other equipment. Do not spray into vents, mechanical or electrical equipment.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions[®] • 1-800-743-6417 PO Box 240014 • Milwaukee, WI 53224 • athea.com



For industrial and commercial use only. For additional information, see Safety Data Sheet.