

**NFPA® RATINGS**

Health: 0; Flammability: 1; Reactivity: 0

**CONTAINS/CAS NUMBER:**

Water/7732-18-5; Acrylic Polymer/Proprietary; Diethylene Glycol Monoethyl Ether/111-90-0; Tributoxyethyl Phosphate/78-51-3; Zinc Oxide/1314-13-2

**DISPOSAL**

Offer empty container for recycling. If recycling is not available, discard container in trash.

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*



Please Recycle.

# TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

## CRYSTAL

Acrylic Floor Finish

- HIGH RESPONSE TO SPRAY BUFFING
- COMBINES EXCEPTIONAL GLOSS, DURABILITY AND REPAIRABILITY IN A SINGLE FINISH

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417  
PO Box 240014 • Milwaukee, WI 53224 • athea.com

**DESCRIPTION**

This finish has been designed to meet the demand for a versatile floor care system that combines good looks, superior durability with ease of maintenance. It applies easily, with no mop drag. Its unique polymer design provides unparalleled responsiveness to spray buffing operations.

**MAINTENANCE:** Dust mop daily using a treated dust mop. Dirt and dust can abrade and scratch your finishes destroying their natural luster. Damp mop regularly, as the highest gloss come only from clean floors. Dirt acts as a barrier to light reflection, causing your floors to look dull and lifeless. To restore lost luster, burnish regularly.

**DIRECTIONS**

Always apply to a floor sealed with a high quality floor sealer. With a clean, rayon/cotton blend mop, apply this product by first “framing” the area to be finished. Use mop to apply a line of seal around the area, then go back and fill in the “framed” area with a gentle side to side mopping motion, being certain to overlap each pass slightly. Apply seal in a thin, unbroken line. If a rectangular finish applicator is being used, be certain that the applicator head has been thoroughly rinsed. Let each coat dry to the touch before recoating. Dry time is approximately 30 minutes. High humidity can prolong dry time. A fan can be used to reduce drying time. Allow the seal to set for 10 minutes before starting a fan. Do not use a fan in areas where dust could be blown onto sealer. Apply each subsequent coat using the same method outlined above. For best results, and for floors subject to spray buffing operations, apply a minimum of two coats of floor finish.

**FLOOR CARE TIPS:**

- To ensure that this product reaches its maximum gloss potential, always apply to floors with at least two coats of a floor seal. Maximum gloss can only be achieved on smooth, level floors. Floor sealers smooth out your floors' surface imperfections to allow for maximum light reflectance.
- Do not use your stripping or rinsing mop or bucket for the application of floor finishes. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of finish.
- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.
- Discard unused finish. Pouring unused finish from your bucket back into the original container can spoil the good finish.

1704.033115