



DANGER

Causes severe skin burns and eye damage. Causes serious eye damage

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

⚠️ WARNING: This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS:

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Butoxyethanol/111-76-2; Potassium Hydroxide/1310-58-3;
Ethanolamine/141-43-5; Pentasodium Triphosphate/7758-29-4

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

CHISEL

Effective Stripping Without
Machine Scrubbing

POTENT FORMULA STRIPS
MACHINE SCRUBBING

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

This product has been carefully formulated to remove heavy accumulations of acrylic, natural or synthetic floor finishes without scrubbing.

FLOOR CARE TIPS:

- Stripping solution should always be prepared just prior to use.
- Always dust mop before starting any stripping operation. Unremoved dirt and dust can damage floors during scrubbing operations.
- Use only cool water when diluting this stripper. Cool water slows down the evaporation of volatile stripping agents to prevent drying on floor.
- Use a small piece of a scrubbing pad or a Doodlebug™ to remove marks.
- Use a separate mop and bucket for stripping and damp mopping operations. Accumulated residues on stripper mop left on floor could prevent bonding of finish coats.

DIRECTIONS

Dust mop entire floor to remove loose dust and dirt. Prepare a stripping solution by diluting 16 to 32 ounces of product per gallon of cool water. Recommended dilution rates are based upon floors with an accumulation of 10 coats of applied floor finish. To ensure proper solution strength, apply diluted product to a small area of floor. Flood floor with stripping solution with a wet mop. Allow the stripping solution to remain on the floor for 5-10 minutes. Do not allow stripping solution to dry on floor. After 5 minutes, agitate stripping solution with stripping mop. This action puts fresh solution in contact with floor to complete the stripping process. Pick up the stripping/finish residue with a wet vac or autoscrubber. Damp mop floor with clean, cool water and a clean mop.



Please Recycle.

1716.083021