

# Loop Treat Poly

Product # 1984

Organic polymer-based scale & corrosion inhibitor

This liquid scale and corrosion inhibitor is designed for use in both hot or cold water closed loop recirculating systems. It features a phosphate-based formula with a polymer dispersant for anti-precipitating and sequestering harmful hard-water scale. It can be injected directly into the recirculating system through the use of a bypass feeder, or applied by use of mild steel piping and feeding equipment.

## Effective Against

- Scale
- Corrosion

## Features and Benefits

- Controls mineral deposits in systems using highly scaling water.
- Built-in color indicator reflects adequate pH levels.

## Properties

Appearance	Red Liquid
Fragrance	Mild
Specific Gravity	1.0
pH	12.0 – 13.0
VOC Content	<0.5% by wt.

## Directions

*Complete directions on product label*  
Typical dosage is 1 gallon for every 125 gallons of capacity. Optimize the dosage by maintaining the phosphate concentration between 3.0 – 5.0 ppm.

## Ingredients

Water  
Potassium Hydroxide  
Amino-Methylene Phosphonic Acid  
Acrylamide-Acrylic Acid Copolymer  
Benzotriazole

## CAS Number

7732-18-5  
1310-58-3  
Withheld  
Withheld  
95-14-7


## Safety

DANGER: Causes severe skin burns and eye damage. Causes serious eye damage.

## DOT Shipping (Ground Transportation)

Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (Potassium Hydroxide)
Class	8
ID Number	UN3266
Packing Group	II

## NFPA® RATINGS



## Quantities

30, 35 & 55 gallon  
5 or 6 gallon  
6 X 1 gallon  
4 X 1 gallon