



DANGER

Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. -No smoking. Avoid breathing spray, vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Immediately call a doctor, POISON CENTER. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

NFPA® RATINGS

Health: 2: Flammability: 2: Reactivity: 0

CONTAINS/CAS NUMBER:

Solvent Naphtha, Med. Aliphatic/64742-88-7; Alkanes, C14-16/90622-46-1 D-limonene/5989-27-5; Fragrance/Mixture

In case of fire: Use carbon dioxide (CO2), dry extinguishing powder foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

For industrial and commercial use only. For additional information, see Safety Data Sheet.



CLEANERS and DEGREASERS

dB SOLVENT HF-165

High Flash Industrial Solvent For Use in Parts Washers

PROVIDE THE STRENGTH TO

DESCRIPTION

If you have been searching for an alternative to chlorinated solvents, there is no need to search further. This product is a blend of natural and synthetic compounds that combine to produce a remarkably effective product. Natural citrus extracts produce incredible solvency to cut through the most difficult deposits. Carefully selected solvents, complete this newest development in industrial solvents.

This product is one of the few products that can remove the strongest deposits without sacrificing workers, safety. The light, fresh scent makes even the most tedious and unpleasant task more bearable.

DIRECTIONS

ADHESIVE REMOVER: This product was developed to safely remove decals, stickers, adhesives and their residues from a variety of surfaces. It works quickly on metal parts without causing corrosion under normal conditions. This product may harm some plastics and painted surfaces, be sure to test before using.

DIP TANK CLEANING: Dip parts to be cleaned into solvent. Allow to soak until grease and grime are loosened. Remove and allow to dry. To reduce drying time, use a compressed air gun. This product may harm some plastics and painted surfaces, be sure to test before using.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/ international regulations.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417 PO Box 240014 • Milwaukee, WI 53224 • athea.com

