



WARNING

Causes skin irritation. Causes serious eye irritation.

This formula is biodegradable and noncorrosive. It will not harm water tanks or fittings and is compatible with all fire fighting foams and tank protectors.

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Alcohol Ethoxylate/68439-46-3; Proprietary/Mixture; Acid Blue 93/28983-56-4; Acid Yellow 23/1934-21-0

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

WATER WETTER

Chemical Additive Increases
the Wetting and
Penetrating Ability
of Water

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

This special wetting agent is designed to help fight stubborn, smoldering fires in upholstery, bedding, paper, hay and brush. Treated water penetrates more quickly, extinguishing the blaze with only 1/3 as much water.

DIRECTIONS

For increasing the wetting ability of water used in fire fighting, use 1/2 - 1 gallon per 100 gallons of water.

This wetting agent also helps to control dust on unpaved roads and yards. Mix 1 - 2 quarts per 100 gallons of water for spraying over road surfaces.

To hold down the dust from mechanical sweepers, add 1 - 2 quarts per 100 gallons of wash water.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.



Please Recycle.

0395.050516